



## PDU15M2F12R Metered PDU

Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

The CyberPower 14-outlet (2 Front and 12 Rear) rack mount metered power distribution unit (PDU15M2F12R) provides 120V 15A output. It distributes power to 14 NEMA 5-15R receptacles from a single NEMA 5-15P input, with unfiltered electrical pass-through. The current draw for connected equipment is displayed in amps on the front LCD for real-time load monitoring.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

### Typical Applications

- Servers
- Network Devices
- Telecom Equipment

### Features

- Metered PDU
- Real-Time Load Monitoring
- Industrial-Grade Metal Housing
- Lifetime Warranty

# PDU15M2F12R Metered PDU

Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

GENERAL	
Type	Metered PDU
Phase	Single Phase
INPUT	
Voltage	120V
Current	15A max
Frequency	50Hz/60Hz
Plug Type	NEMA 5-15P
Plug Style	Straight
Cord Length	15'
OUTPUT	
Nominal Output Voltage	120V
Outlets - Total	14
Outlet Type	NEMA 5-15R
Outlets - Front	2
Outlets - Rear	12
Meter Readout	Amperage
Overload Protection	15A
PHYSICAL	
Rack Size	1U
Form Factors Supported	1U Rackmount, 0U Vertical Rackmount, Undercounter Installation Supported
Cord Retention Organizers	Yes
External Site Ground Pin	Yes
Adjustable Mounting Brackets	2 sets (L-short, L-long)
Dimensions (WxHxD) (in.)	17.5 x 1.75 x 2.25
Weight (lbs.)	4.0
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL1363 certified by ETL (USA), CSA C22.2 (Canada)
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Lifetime