

# DC BLOWER 75x77x30mm



**Housing/Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 10MΩ, 500VDC/min between bare wire and frame  
**Dielectric Strength:** 5mA max. 500VAC/min between bare wire and frame  
**Operation Temperature:** -10°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~70°C(Humidity 35%-85%RH)  
**Lead Wire:** UL Type #24 AWG  
**Weight:** 87 g      **Packing:** 100PCS/CTN



Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD7530B12W3-61	▲ 12	6.0~13.8	7.30	4.00	25.60	2,000	90	1.08	B,S	①
FBD7530B12W5-61	▲ 12	6.0~13.8	9.40	7.10	32.50	2,500	170	2.04	B,S	②
FBD7530B12W7-61	★▲ 12	6.0~13.8	11.30	11.20	37.40	3,000	250	3.00	B,S	③
FBD7530B12W9-61	★▲ 12	6.0~13.8	13.30	16.10	42.40	3,500	320	3.84	B,S	④
FBD7530B12W11-61	★▲ 12	6.0~13.8	14.30	19.70	44.30	3,800	460	5.52	B,S	⑤
FBD7530B24W3-61	▲ 24	12.0~27.6	7.30	4.00	25.60	2,000	80	1.92	B,S	①
FBD7530B24W5-61	▲ 24	12.0~27.6	9.40	7.10	32.50	2,500	100	2.40	B,S	②
FBD7530B24W7-61	★▲ 24	12.0~27.6	11.30	11.20	37.40	3,000	130	3.12	B,S	③
FBD7530B24W9-61	★▲ 24	12.0~27.6	13.30	16.10	42.40	3,500	150	3.60	B,S	④
FBD7530B24W11-61	★▲ 24	12.0~27.6	14.30	19.70	44.30	3,800	230	5.52	B,S	⑤

- For "Sleeve" bearing version, change the "B" in the model number to, "S".
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

