

# Rittal – The System.

Faster – better – everywhere.



## KX 1577.000

## E-box KX, carbon steel

State: 6/13/2024 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# KX 1577.000 - E-box KX, carbon steel

The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.

## Features

Model No.	KX 1577.000
Product description	The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.
Material	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting panel: Zinc-plated
Color	RAL 7035
Supply includes	Housing with door Mounting panel Cam lock with 3 mm double-bit insert 180° hinge
Protection category NEMA	NEMA 1, 3R, 4, 12
Protection category IP to EN 60 529	IP 66
Type rating according to UL 50E	Type 1, 3R, 4, 12
IK code	IK08
Dimensions	Width: 300 mm Height: 400 mm Depth: 155 mm Width: 11.8 " Height: 15.7 " Depth: 6.1 "
Dimensions of mounting plate (W x H)	275 mm x 385 mm 10.8 " x 15.2 "

## Features

Material thickness - enclosure	1.25 mm 0.05 "
Material thickness - door	1.25 mm 0.05 "
Material thickness – mounting plate	2 mm 0.08 "
Lock	No. of locks: 1
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	6.98 kg 15.4 lb.
Customs tariff number	94032080
EAN	4028177816633
E-Number Sweden	E3465239
ETIM 7.0	EC000261
ECLASS 8.0	27180101

## Approvals

Approvals	Bureau Veritas DNV-GL Lloyds Register of Shipping UL + C-UL (listed)
Certificates	Protection category
Explanations	Manufacturer's declaration Declaration of conformity Declaration of conformity UK