1747996-4 ✔ ACTIVE


GRACE INERTIA 12.4


TE Internal #: 1747996-4

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 2 Position, 12.4 mm [.488 in] Centerline, Printed Circuit Board, GRACE INERTIA 12.4

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors







Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **2**

Centerline (Pitch): **12.4 mm [.488 in]**

Features

Product Type Features

Header Type	Fully Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	2
PCB Mount Orientation	Vertical
Number of Power Positions	2
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VDC

Body Features

Connector & Keying Code	D

Contact Features

Contact Layout	Inline
Mating Tab Width	3.1 mm[.122 in]
Contact Mating Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	20 A
Contact Retention Within Housing	With
Contact Type	Tab
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.8 µm[31.5 µin]

Termination Features

Termination Post & Tail Length	3.1 mm[.122 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention Type	Latch
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	12.4 mm[.488 in]
Housing Color	Yellow
Housing Material	Nylon 6/6 GF

Dimensions

Connector Height	10.7 mm[.421 in]

Wire Size	2427 - 7144 CMA

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]

Operation/Application

Circuit Application	Power

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	150
Packaging Method	Bag

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1747996-2
GHC EYELET 12.4 2POS HEADER ASSY RED



TE Part # 1747996-1
GHC EYELET 12.4 2POS HEADER ASSY NATURAL



TE Part # 1747995-4
GHC EYELET 6.2 3POS PLUG HOUSING YELLOW

Also in the Series | GRACE INERTIA 12.4



Rectangular Power Connectors(4)

Customers Also Bought



TE Part # 2-1971905-5
PLUG HOUSING 10POS,KEYING-B, NEW GIC3.3



TE Part # 2-172210-6
PL MKII 187 REC HSG 2P BLUE



TE Part # 1376383-6
5.0 PK CONN 3P HDR ASSY HIGH CURRENT



TE Part # 2-2360547-5
SGI 1.5 HDR, 5P, VT, Key B, Black



TE Part # 2-2371404-7
SGI 1.25 Plug HSG, 7P, Key B, Black



TE Part # 2-2382946-5
SGI 1.5 Plug HSG, 5P, Key B, Black

TE Part # 2357090-1
GRACE INERTIA 3.5W CAP 8P NAT

TE Part # 2357091-1
GRACE INERTIA 3.5W TPA 4P

TE Part # 2357092-1
GRACE INERTIA 3.5W PLUG 10P NAT

TE Part # 2357097-1
GRACE INERTIA 3.5W TPA 6P

Documents

Product Drawings

GHC EYELET 12.4 2POS HEADER ASSY YELLOW

English

CAD Files

Customer View Model

ENG_CVM_CVM_1747996-4_F.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1747996-4_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1747996-4_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Product Specifications

Application Specification

English