
Your Expert Partner for **Human Machine Interfaces**

Actuator

Distribution by
DigiKey

51-
376.F22D



https://digikey.eao.com/p/51-376.F22D

Your product:



51-376.F22D
Actuator

FRONT

Front dimension:	Ø 18 mm

MOUNTING

Design:	raised

ELECTRICAL CHARACTERISTICS

Thermal current Ith:	5 A, according to EN / IEC 60947-5-1
Switching voltage and switching current:	250 VAC, 5 A (cosφ 0.75)
Contacts:	2 NC / 2 NO
Protection class:	II
Electrostatic discharge (ESD):	≤ 15 KV
Electric strength:	2500 VAC, 50 Hz, 1 min. between all terminals and earth, according to IEC 61058-1, part 15

MECHANICAL CHARATERISTIC

Switching system:	Self-cleaning, double-break snap action switching system, 2 normally closed and 2 normally open contact per element.
Terminal:	Plug-in terminal, 2.8 x 0.5 mm
Wire cross section:	Max. wire cross-section 2 wires with 1 mm Max. wire cross-section of stranded cable 2 x 0.75 mm^2
Contact material:	Gold
Mechanical lifetime:	50 000 cycles of operation
Switching action:	Momentary - Rest (a) - Maintained (a)
Switching positions:	3 positions

Weight:	0.016 kg
Tightening torque:	Fixing nut max. 0.5 Nm
Switching angle:	42° left / 90° right
Switching system:	Snap-action switching element

AMBIENT CONDITION

Operating temperature:	– 25 °C ... + 55 °C
IP front protection:	IP65, according to DIN EN 60529
Storage temperature:	– 40 °C ... + 85 °C


CERTIFICATE

Approbations:	CB (IEC 61058-1), CQC, CSA, DNV, ENEC (EN 61058-1), UL


OTHER

Short Description:	Actuator, Ø 18 mm, 2 NC / 2 NO, Momentary - Rest (a) - Maintained (a), Plug-in terminal, 2.8 x 0.5 mm, IP65, according to DIN EN 60529
Hints:	Standard lock: DOM 311


Dimension drawings:



Mounting cut-outs:



Wiring diagrams:



Switching positions:

