



SMUCB100UAC | 3-PHASE MODULAR UPS CIRCUIT BREAKER

Ensure safe operation for your equipment and personnel with proper over-current protection

The CyberPower SMUCB100UAC 3-Phase Modular UPS Circuit Breaker Hardware provides convenience and safety with optional 20KVA UPS Input/Output. If the input side overcurrent protection device is in a different area of your facility, having the input circuit breaker at the UPS adds an extra disconnect point for easy bypass during repairs or maintenance. The output circuit breaker also provides protection if your load is connected directly to the UPS without an appropriate overcurrent protection device. Includes a One-Year Limited Warranty.

For CyberPower Smart App Online 3-Phase Modular UPS system SM020KAMFA.



SPECIFICATIONS

PHYSICAL	
Color	White/Gray
Form Factor	Modular
Material of Construction	Metal
Mounting Hardware	Yes

PHYSICAL DIMENSIONS	
Physical Dimensions - WxHxD (cm)	7.62 x 12.95 x 8.38 cm
Physical Dimensions - WxHxD (in.)	3.00 x 5.10 x 3.30 in.
Weight (kg)	1.1 kg
Weight (lb)	2.43 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	9.22 x 11.43 x 13.97 cm
Shipping Dimensions - WxHxD (in)	3.63 x 4.5 x 5.5 in.
Weight (kg)	1.09 kg
Weight (lb)	2.4 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Elevation Note	At $\leq 1,000\text{m}$ above sea level, de-rate power by 1% per 100m between 1,000m and 3,048m
Operating Relative Humidity	0 - 95% (non-condensing)
Operating Temperature	32 - 104°F (0 - 40°C)
Operating Temperature Note	Battery life is halved for every 50°F (10°C) increase above 68°F (20°C)
Storage Battery Temperature Note	Optimum battery storage between 5 - 68°F (-15 - 20°C)
Storage Relative Humidity	0 - 95% (non-condensing)
Storage Temperature	-4 - 158 °F (-20 - 70 °C)

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL489/CSA C22.2/CE CCC IEC 60947-1 IEC 60947-2 EN 50581

WARRANTY	
Product Warranty	One-Year Limited Warranty