



Meets ANSI/ESD S20.20 and Packaging Standard ANSI/ESD S541

Features

- Constructed from extruded honey-comb structure of high impact polypropylene material yielding superior strength and durability
- Conductive material $< 1 \times 10^4$ ohms provides a reliable path-to-ground
- Printed with ESD protective symbol as required by ANSI/ESD S541
- Provides durable, physical protection
- Efficient means of transporting static sensitive items
- Static dissipative foam bottom laminated to Endura-Tek™, provides ESD and shock protection
- Includes steel reinforcing frame and rolled over side construction (double thickness) for greater durability
- Trays stack together, improving productivity and saving valuable work space
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- Reusable, ensuring best value
- Product ships assembled
- Made in the United States of America

Specifications

Properties

Resin Type

Conductive

Surface Resistivity

Material Thickness

Melting Temperature

Heat Deflection

Typical Values

Polypropylene

Inherently

$< 1 \times 10^4$ ohms per ANSI/ESD STM11.11 and ESD TR53

4.0 mm

320° F

185° F

Per Packaging standard ANSI/ESD S54.1 section 6.1. Inside an ESD Protected Area "Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact."

Item	Size I.D. L x W x D (IN)	Size I.D. L x W x D (MM)
39410	18 x 11-3/8 x 1-3/4	457 x 289 x 44
39411	22-3/4 x 17-1/2 x 2-1/2	578 x 445 x 64

Unless otherwise noted, tolerances are $\pm 1/16"$



Made in the United States of America

Specifications and procedures subject to change without notice.

ENDURA-TEK™ TEK TRAYS

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
39410

DATE:
June
2024