Your Expert Partner for **Human Machine Interfaces**

Actuator

Distribution by
DigiKey

31-
710.0292



https://digikey.eao.com/p/31-710.0292

Your product:



31-710.0292
Actuator

FRONT

Front bezel colour:	Black
Front form:	square
Front dimension:	18 mm x 18 mm
Front bezel material:	Plastic

MOUNTING

Mounting cut-out:	Ø 16 mm
Design:	raised

OPERATING-/INDICATION PART

Lens illumination:	illuminative

ELECTRICAL CHARACTERISTICS

Protection class:	II
Standards:	According to EN/IEC 61058-1
Rated Operational Voltage Ue:	250 VAC/VDC
Switching voltage and switching current:	250 VAC, 5 A (ohmic) 250 VAC, 3 A (Soldering terminal) 250 VAC, 2 A (inductive, cos(phi) = 0.7) 125 VAC, 3 A (inductive, cos(phi) = 0.7) 220 VDC, 0.1 A (inductive, L:R = 30 ms) 60 VDC, 0.7 A (inductive, L:R = 30 ms) 24 VDC, 2 A (inductive, L:R = 30 ms)
Electrical lifetime:	50 000 cycles of operation
Contacts:	1 NC / 1 NO
Electric strength:	

2500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

Thermal current Ith:	5 A

MECHANICAL CHARATERISTIC

Switching system:	Self-cleaning, double-break snap action switching system (contact opening width 2 mm x 0.5 mm), 1 normally closed and 1 normally open contact per element.
Operating Travel:	ca. 3 mm
Switching system:	Snap-action switching element
Mechanical lifetime:	2 Mio. cycles of operation
Switching action:	Momentary
Contact material:	Gold
Operating force:	2 N ... 5,5 N, depending on the number of switching elements
Tightening torque:	Fixing nut max. 0.5 Nm
Weight:	0.008 kg
Terminal:	Universal soldering terminal

AMBIENT CONDITION

Storage temperature:	– 40 °C ... + 85 °C
Shock resistance:	15 g for 11 ms, as per IEC 60512-4-3, IEC 60068-2-27 (Single impacts, semi-sinusoidal)
Climate resistance:	Standard condition according to IEC 60068-2-3 Changing condition according to IEC 60068-2-14
Operating temperature:	– 25 °C ... + 55 °C, mounted as a block, make sure the heat can escape freely
Vibration resistance:	10 g at 10 Hz...2000 Hz, amplitude 1.5 mm (Sinusoidal), according to DIN EN 60512-4-4, DIN EN 60068-2-6
IP Protection:	IP40 front side, IP67 with front protective cap

CERTIFICATE

Approbations:	CB (IEC 61058-1), CSA, DNV, ENEC (EN 61058-1), UL
Conformities:	CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

OTHER


max. number of switching elements:	1

Housing colour: Black


Short Description: Actuator, Ø 16 mm, 18 mm x 18 mm, illuminative, square, Black, Plastic, 1 NC / 1 NO, Momentary, Universal soldering terminal

Internal size: 15,3 mm x 15,3 mm


Component layouts:



Wiring diagrams:



Mounting cut-outs:



Dimension drawings:

