


| Assembly Specifications |                 |
|-------------------------|-----------------|
| Temp Rating             | -20 to 80 C     |
| Max Voltage             | 60V             |
| Max Current             | 3A              |
| IP Protection           | IP 67           |
| Length (L)              | 394in / 10008mm |
| Tolerance               | +4.0in -4.0in   |


| Wiring Schematic |                 |         |
|------------------|-----------------|---------|
| A Pin #          | Conductor Color | B Pin # |
| 1                | Black           | 1       |
| 2                |                 | 2       |
| 3                | Blue            | 3       |
| 4                | Orange          | 4       |
| 5                |                 | 5       |
| 6                |                 | 6       |
| 7                |                 | 7       |
| 8                |                 | 8       |
| Shield           | Attached        | Shield  |

| Cable Specifications |                |
|----------------------|----------------|
| Cable Jacket         | PVC            |
| Cable OD             | 0.19in / 4.8mm |
| No. /Gauge           | M46B-424       |
| Conductor Jacket     | PVC            |
| Shielding            | Yes            |

### A SIDE



### B SIDE



### Notes

- 1) Connector pin view is from front of connector
- 2) Not for interrupting current
- 3) Some options and features may not be shown
- 4) Additional technical details available upon request; Consult Factory
- 5) Dimension in parentheses are for reference only



Date Gen: 4/18/24

| REV | BY  | DATE     | DESCRIPTION        |
|-----|-----|----------|--------------------|
| 0   | MMG | 01/04/22 | Initial Release    |
| 1   | MMG | 03/16/22 | Production Release |

Tolerance Unless  
Otherwise Specified  
0.00 = +/- 0.13  
0.000 = +/- 0.050  
ANGLES = +/- 5  
Secondary Unit for  
Reference Only



1200 East St, Fairport, OHIO 44077  
PH: (440) 350-1230 [www.mjmindustries.com](http://www.mjmindustries.com)

Part Number:  
**M08A03F1-0394B-X02**

Description:  
M08 A Coded 3 Position Female Straight to Flying  
Leads with 394in of PVC Cable