

DESCRIPTION: M12 // F // SC // 3P // ROTATED // SHIELDED // CABLE MOUNT

SPECIFICATIONS:

MATERIALS:
HOUSING: PBT, UL94 V-0, BLACK
CONTACTS: GOLD PLATED BRASS (SEE PART NUMBER KEY)

NUT: NICKEL PLATED BRASS
SHELL: NICKEL PLATED BRASS
ORING: EPDM

ELECTRICAL:
RATED CURRENT: 4A
RATED VOLTAGE: 250V
INSULATION RESISTANCE: 100 MOhms MIN.
CONTACT RESISTANCE: 10 mOhms MAX.

ENVIRONMENT:
OPERATING TEMPERATURE: -40°C TO +85°C
WATER PROOF: IP67

MAX WIRE AWG: 20


NORCOMP MATING PART NUMBERS:

858-003-103RKT4*
858-R03-103RLU4*
858-R03-103RSS4*
859-R03-103R004*
860-003-113R004*
861-R03-113R004*
*Also all material and contact plating variants

858-R03-203RSSY

3 = BRASS/NICKEL NUT
S = STAINLESS STEEL NUT & SHELL

1 = GOLD FLASH
4 = 10u" GOLD



RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
J. KADEL

DATE:
09/09/2020

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE:
NTS

SHEET 1 OF 1

REV 4

DWG NO.

858-R03-203RSSY