

SEALED 1/4" MINI JACK MODEL S1K



Many types of professional music equipment nowadays use high power components, and need to be cooled by fans. Fans draw in dust and pollutants which can adversely affect the contacts of conventional jacks, with exposed contacts.

S1K avoids possibility of contamination of contacts by means of a sealing cover over the top and bottom of the jack. The height profile and PCB fitting are the same as our standard S1 jacks.

S1K is available with switched mono /BNB or stereo /BBB configurations and types of front bush. Other contact configurations can be made subject to quantity. Plastic nut is standard.

MODELS

S1KA Standard fully threaded for plastic or metal nut.

S1KB SPN - Partially reduced nose. Nuts not usually used, but are supplied.

UNF

14.5 12.7

S1KC Full thread with discrete bright insert and isolated RFI washer

S1KD Full thread with prominent bright insert. RFI washer connected to inserted jack plug.

S1KE Non thread bush. Nuts not used.

<u>21.5</u> 33.2

Retained hole plug forming a seal for front is available as an accessory.

ø7/16″

20TPI









FC67810 S1KA/BBB/WNW SEALED JACK STD FC67815 S1KA/BNB/WNW SEALED JACK STD S1KB/BBB/WNW/SPN SEALED JACK FC67820 FC67825 S1KB/BNB/WNW/SPN SEALED JACK S1KC/BBB/NI/WN/IEW SEALED JACK FC67830 FC67835 S1KC/BNB/NI/WN/IEW SEALED JACK FC67840 S1KD/BBB/NI/WN/CEW SEALED JACK S1KD/BNB/NI/WN/CEW SEALED JACK Fc67845 FC67850 S1KE/BBB/NNW SEALED JACK PLAIN S1KE/BNB/NNW SEALED JACK PLAIN FC67855 FC67858 S1K FRONT SEAL

1.5 (6x)




ß



SWITCH CONTACTS OPEN WHEN PLUG IS INSERTED, CLOSE WHEN PLUG IS WITHDRAWN.

IEW = isolated earth washer CEW = connected earth washer



SPECIFICATION

Withstand Voltage: Maximum Current: Temperature Rating: Life >10000 operations: Initial Contact Resistance: IP Rating (with plug in): 2000VDC Min. 5A. -10°C ~ +70°C Contact resistance <100m Ω <50m Ω IP50



Black socket showing hole seal.

Order as:

© CLIFF 01/18 ISS.4

S1K[]/BNB - Mono BBB - Stereo

RoHS / REACH compliant All models, except type E,supplied with plastic nut and washer 100 / Tray / 1000 / Carton

For further information, contact sales@cliffuk.co.uk

Cliff Electronic Components Limited,

Type

76 Holmethorpe Avenue, Holmethorpe Ind. Estate, Redhill, Surrey RH1 2PF U.K. Tel: +44 (0)1737 771375 Fax: +44 (0)1737 766012

www.cliffuk.co.uk



