

03 0382


Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP68



Shielding or ground contact ring for chassis plugs and sockets with front mounting

03

0382



#### Environmental conditions

Temperature range -40 °C/+85 °C

#### Materials

Component CuZn, pre-nickel and tin-plated

#### Associated products

##### Accessories

<a href="#">☞ 0304</a>	<a href="#">☞ 0304-1</a>	<a href="#">☞ 0304-2</a>
<a href="#">☞ 0306</a>	<a href="#">☞ 0306-1</a>	<a href="#">☞ 0306-2</a>
<a href="#">☞ 0314</a>	<a href="#">☞ 0314-1</a>	<a href="#">☞ 0314-2</a>
<a href="#">☞ 0316</a>	<a href="#">☞ 0316-1</a>	<a href="#">☞ 0316-2</a>
<a href="#">☞ 0362</a>	<a href="#">☞ KFR</a>	<a href="#">☞ KfV</a>
<a href="#">☞ KfV ... C</a>	<a href="#">☞ SFV</a>	<a href="#">☞ SFV ... C</a>

[☞ Weitere Produkte auf Anfrage](#)

03

0382

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
0382	-	50	500

**Packaging:**

in a cardboard box