

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

CUSTOMER : _____

MODULE NO.: **WWSTLINKV3MODS-00#**

APPROVED BY: (FOR CUSTOMER USE ONLY)	PCB VERSION: DATA:
--	---

SALES BY	APPROVED BY	CHECKED BY	PREPARED BY
			Hedy Lai
ISSUED DATE: 2024/05/14			

TFT Display Inspection Specification: <https://www.winstar.com.tw/technology/download.html>

Precaution in use of TFT module: <https://www.winstar.com.tw/technology/download/declaration.html>



RECORDS OF REVISION			DOC. FIRST ISSUE
VERSION	DATE	REVISED PAGE NO.	SUMMARY
0	2024/05/14		First issue

WINSTAR DISPLAY CO., LTD

Contents

1.Module Classification Information

2.Summary

3.General Specification

4.Electrical Characteristics

5.Interface

6.Contour Drawing

1.Module Classification Information

W	W	STLINKV3MODS	-	00	#
①		②		③	④

①	Brand : WINSTAR DISPLAY CORPORATION				
②	Controller: STLINK-V3MODS				
③	Version: 00				
④	Special Code	#:Fit in with ROHS directive regulations			

2.Summary

The WWSTLINKV3MODS-00# is an accessory for Winstar Smart Display CAN series Demo Set. It allows users to experience the exclusively developed GUI Builder. By operating the GUI Builder software on your computer, you can design a user interface (UI) without writing any programs. Then, you can use the dongle to transfer the UI to the Smart Display for display, reducing development costs and speeding up time-to-market expectations. This module is suitable for fast and easy integration of a human-machine interface (HMI) into various applications, including passenger vehicles, industrial automation, mechanical control, elevators, escalators, and electronic equipment for aviation and navigation. The module is also compliant with RoHS regulations

1. Self-powered via a USB Micro-B connector
2. Bridge USB to CAN using 2-wire locking connector
3. Demonstration video link: <https://www.winstar.com.tw/video/play/142.html>

3.General Specifications

Item	Dimension	Unit
Module dimension	30.0 × 60.0 × 13.0 (Max)	mm
Interface	Micro-B USB	

4. Electrical Characteristics

4.1 Supply Conditions

Parameter	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Supply Voltage	VDD	4.5	5	5.25	V	USB Power
Supply Current	IDD	—	0.11	—	mA	Note

Note : This typical value is at $T_A = 25^{\circ}\text{C}$ and $V_{DD} = 5\text{V}$.

4.2 CAN Transmit Data Input Conditions

Parameter	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Low level input voltage	V_{IL}	-0.3	—	0.8	V	
High level input voltage	V_{IH}	2	—	5	V	

5.Interface

CAN			
Pin	Symbol	I/O	Function
1	CAN_High	I/O	CAN bus D+
2	CAN_Low	I/O	CAN bus D-

Note : This is a locking connector that can be pulled out smoothly by simply pressing it.



6. Contour Drawing

