
RSC10-4-3-A

Ruland RSC10-4-3-A, 0.250" x 0.188" Short Slit Coupling, Aluminum, Clamp Style, 0.630" OD, 0.778" length





Description

Ruland RSC10-4-3-A is a clamp style slit coupling with 0.2500" x 0.1875" bores, 0.630" OD, and 0.778" length. It is manufactured from a single piece of material and has two sets of intermittent slit cuts allowing for a maintenance-free coupling with high torsional stiffness in relation to comparable couplings, such as beam type. RSC10-4-3-A is commonly used in precise positioning applications found in semiconductor, medical, and test and measurement equipment. This short style slit coupling is ideal for compact installations where the long type may not fit. It is a suitable alternative to comparatively sized disc couplings due to the ability to accommodate all forms of misalignment whereas a single disc coupling has no accomodation for parallel misalignment. RSC10-4-3-A is zero-backlash, has a balanced design for reduced vibration at speeds up to 10,000 RPM, and can accommodate all forms of misalignment with light bearing loads. It is manufactured by Reliance Precision Ltd. in their County Cork, Ireland factory from 7075 aluminum for lightweight and low inertia. RSC10-4-3-A is inventoried by Ruland and RoHS3 and REACH compliant.

Product Specifications

Bore (B1)	0.2500 in	**Small Bore (B2)**	0.1875 in
B1 Max Shaft Penetration	0.311 in	**B2 Max Shaft Penetration**	0.311 in
Outer Diameter (OD)	0.630 in	**Bore Tolerance**	+0.001 in / -0.000 in
Length (L)	0.778 in	**Clearance Diameter (C) MAX**	0.709 in
Cap Screw	M2	**Screw Material**	18-8 300 Series Stainless Steel
Hex Wrench Size	1.5 mm	**Screw Finish**	Bright
Seating Torque	0.36 Nm	**Number of Screws**	2
Dynamic Torque Reversing	4.9 lb-in	**Angular Misalignment**	2.5°
Dynamic Torque Non-Reversing	7.5 lb-in	**Parallel Misalignment**	0.004 in
Peak Torque	11 in-lb	**Axial Motion**	0.016 in
Torsional Stiffness	10.6 lb-in/Deg	**Moment of Inertia**	0.000989 lb-in²
Maximum Speed	10,000 RPM	**Full Bearing Support Required?**	Yes
Zero-Backlash?	Yes	**Balanced Design**	Yes
Material Specification	7075-T651 Extruded and Drawn Aluminum Bar	**Temperature**	-110°F to 175°F (-80°C to 80°C)
Finish Specification	SurTec 650	**Manufacturer**	Reliance Precision Limited
Country of Origin	Ireland	**Weight (lbs)**	0.017300
UPC	634529298190	**Tariff Code**	8483.60.8000
UNSPC	31163003		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65			

⚠**WARNING** This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.