



**STANDARD ENERGY MAGNETIC STRIP WITH NPSA ADHESIVE (.030" / .057")**

**Features:**

From ¼" to 3" wide

**Standard energy magnetic base, black surface**

Works using magnetic principle with iron or steel material.

Will not demagnetized, anti-rust

Adhesive is a premium permanent outdoor acrylic adhesive on the back., with white PE liner

Excellent for durable indoor displays, such as retail displays

Material on 3" core (12" outside diameter)

Code	Size	Gross weight	Total thickness	Pull strength
060A-1/4	.057" x ¼" x 100'	2.5 lbs	.062"	>3 lb/liner foot
060A-1/2	.057" x 1/2" x 100'	5 lbs	.062"	>6 lb/liner foot
060A-3/4	.057" x 3/4" x 100'	7.5 lbs	.062"	>9 lb/liner foot
060A-1	.057" x 1" x 100'	10 lbs	.062"	>13 lb/liner foot
060A-2	.057" x 2" x 100'	20 lbs	.062"	>26 lb/liner foot
060A-3	.057" x 3" x 100'	30 lbs	.062"	>39 lb/liner foot
030A-1/2	.030" x 1/2" x 200'	5 lbs	.034"	>4.5 lb/liner foot
030A-3/4	.030" x ¾" x 200'	7.5 lbs	.034"	>6.5 lb/liner foot
030A-1	.030" x 1" x 200'	10 lbs	.034"	>9 lb/liner foot
030A-2	.030" x 2" x 200'	20 lbs	.034"	>18 lb/liner foot

UV	Latex	(Eco)Solvent	Offset/Flexo	Screen	Dye/Pigment	Toner Based
n/a	n/a	n/a	n/a	n/a	n/a	n/a

**Application and storage conditions:**

**Working condition:** temperature 15°C/59°F to 30°C/86°F, and relative humidity 30% to 60%

**Storage condition:** closed preserve avoiding sunlight, in temperature 10°C/50°F to 35°C/95°F, relative humidity 20% to 70%

**Shelf life:** 12 months under normal storage conditions. Unfinished material should be re-packed, and used up within one month.

**Adhesion date:**

**GB/T 2792-1998** – 180°, adhesion to stainless steel, 30 minutes RT: N/25mm – 8

**Notice:**

Before installation, make sure the wall surface is clean, dry and flat