



PLAIN BROWN HIGH ENERGY MAGNETIC SHEETING (.030"/.040")

Features:

Our high energy magnetic sheeting has 2.6 times more magnetic energy than standard magnetic sheeting
Up to 50" wide format
Plain brown on both sides
Will not demagnetized, anti-rust
Easy to apply to apply, remove and change, without leaving residue
Material on 3" core, in a lid-tray box

Code	Size	Gross weight	Total thickness	Pull strength
HE030PB/100MP	.030" x 24.375" x 50'	65 lbs	.030"	>144
HE040PB/100MP	.040" x 24.375" x 50'	90 lbs	.040"	>185

UV	Latex	(Eco)Solvent	Offset/Flexo	Screen	Dye/Pigment	Toner Based
N/A	N/A	N/A	N/A	N/A	N/A	N/A

Application and storage conditions:

Working condition: temperature 15°C/59°F to 30°C/86°F, and relative humidity 30% to 60%

Storage condition: closed preserve avoiding sunlight, in temperature 10°C/50°F to 35°C/95°F, relative humidity 20% to 70%

Shelf life: 12 months under normal storage conditions. Unfinished material should be re-packed, and used up within one month.

Physical data:

Water resistance: High

Working temperature: -15°F to +176°F

Flexibility at 68°F: can be coiled to a ½" diameter without cracking

SIMPLE SIGNMAN division of Decalcorama Inc.
5305 Trudeau St-Hyacinthe QC J2S 7W9
Phone : 1 866 MAGNET 8