

PRINTABLE MAGNETIC SHEETING PVC (.010" / .012" / .015" / .020" / .030")

Features:

Up to 60" wide format

4 mil thick white matte PVC vinyl bonded to magnetic sheeting

Suitable for UV/Solvent/Eco-solvent printing

Great white point for accurate printing

Will not demagnetized, anti-rust

Easy to apply to apply, remove and change, without leaving residue

Material on 3" core, in a lid-tray box

Code	Size	Gross weight	Total thickness	Pull strength
010WM/24	.010" x 24.375" x 100'	48 lbs	.014"	>26 lb/sq2
010WM/40	.010'' x 40'' x 100'	80 lbs	.014"	>26
010WM/50	.010'' x 50'' x 100'	100 lbs	.014"	>26
012WM/24	.012" x 24.375" x 100'	56 lbs	.016"	>33
015WM/24-V	.015" X 24.375" X 50'	35 lbs	.019"	>41
015WM/40	.015" x 40" x 50'	59 lbs	.019"	>41
015WM/48	.015" x 48" x 50'	70 lbs	.019"	>41
015WM/50	.015" x 50" x 50'	73 lbs	.019"	>41
015WM/60	.015" x 60" x 50'	89 lbs	.019"	>41
020WM/24-V	.020'' x24.375'' x 50'	45 lbs	.024"	>55
020WM/40	.020" x 40" x 50'	75 lbs	.024"	>55
020WM/48	.020'' x 48''x 50'	90 lbs	.024"	>55
020WM/50	.020" x 50" x 50'	94 lbs	.024"	>55
030WM/24-V	.030" x 24.375" x 50'	65 lbs	.034"	>92
030WM/30	.030" x 30" x 50'	82 lbs	.034"	>92
030WM/40	.030" x 40" x 50'	109 lbs	.034"	>92
030WM/48	.030" x 48" x 50'	130 lbs	.034"	>92
030WM/50	.030" x 50" x 50'	136 lbs	.034"	>92

UV	Latex	(Eco)Solvent	Offset/Flexo	Screen	Dye/Pigment	Toner Based
Yes	Test required	Yes	Yes	Yes	No	No

Application and storage conditions:

Working condition: temperature 15°C/59°F to 30°C/86°F, and relative humidity 30% to 60%

 $\textbf{Storage condition:} \ closed \ preserve \ avoiding \ sunlight, in \ temperature \ 10°C/50°F \ to \ 35°C/95°F, \ relative \ humidity$

20% to 70%

Shelf life: 12 months under normal storage conditions. Unfinished material should be re-packed, and used up within one month.