



HIGH ENERGY MAGNETIC SHEETING WITH PSA ADHESIVE (.030")

Features:

Up to 48" wide format

High energy magnetic base, black surface, works with magnetic receptive print media

Works using magnetic principle with iron or steel material.

Will not demagnetized, anti-rust

Easy to apply to apply, remove and change, without leaving residue

Excellent for durable indoor displays, such as retail displays

Material on 3" core, in a lid-tray box

Code	Size	Gross weight	Total thickness	Pull strength
HE030PSA/100	.030" x 24.375" x 50'	65 lbs	.034"	>133 lbs/ft2

UV	Latex	(Eco)Solvent	Offset/Flexo	Screen	Dye/Pigment	Toner Based
n/a	n/a	n/a	n/a	n/a	n/a	n/a

Application and storage conditions:

Working condition: temperature 15°C/59°F to 30°C/86°F, and relative humidity 30% to 60%

Storage condition: closed preserve avoiding sunlight, in temperature 10°C/50°F to 35°C/95°F, relative humidity 20% to 70%

Shelf life: 12 months under normal storage conditions. Unfinished material should be re-packed, and used up within one month.

Adhesion date:

GB/T 2792-1998 – 180°, adhesion to stainless steel, 30 minutes RT: N/25mm – 8

Notice:

Before installation, make sure the wall surface is clean, dry and flat