


PART NUMBER: 1476

SysSPEED® Premium Network EtherNet/IP Cable
Cat 6A+ Unshielded Twisted Pair (UTP) 4 Pair 23 AWG
Riser Rated - CMR, FT4, Sunlight Resistant



CHARACTERISTICS

- ▶ **Conductor:** 23 AWG Solid Bare Annealed Copper
- ▶ **Insulation:** Premium Polyolefin
- ▶ **Spline:** Premium Polyolefin
- ▶ **Rip Cord:** Applied Longitudinally Under Jacket
- ▶ **Jacket:** Premium PVC (Flame-Retardant, Sun Resistant & RoHS Compliant)

- ▶ **Nominal Cable Diameter (in):** 0.245
- ▶ **Temperature Rating (°F):**
Installation: +32 to +140
Storage & Operation: -4 to +167
- ▶ **Operating Voltage:** 300V Max
- ▶ **Recommended RJ45 Connector:**
Platinum Tools # ezEX48

Conductor Color Code

- Pair 1:** Blue - White/Blue
- Pair 2:** Orange - White/Orange
- Pair 3:** Green - White/Green
- Pair 4:** Brown - White/Brown

FEATURES & BENEFITS

- ▶ Cable is flexible and easy to install
- ▶ RhinoPac® packaging prevents cable tangling, crushing, and water damage
- ▶ For applications that require Optimum Cat 5e Performance with flexibility for the future
- ▶ Third-party verified for guaranteed performance and RoHS compliance
- ▶ Free from restricted metals and hazardous compounds. Check our green leaf label for more information
- ▶ Combines indoor/outdoor applications into one product. Complies with UL1581 sunlight resistance requirement for outdoor installations (Do not use as a substitute for Underground Direct Burial Cables)



APPLICATIONS

Premise Horizontal Cable, Wireless, WIFI, 10 Gigabit Ethernet, IEEE 802.3:1000 BASE-T Gigabit Ethernet, 100 BASE-TX, 10 BASE-T, 155 Mb/s and 622Mb/s ATM, ANSI X 3.263: 100Mb/s, Broadband Baseband Analog Video and transport of High Definition 1920 X 1080p Ultra-High Definition 4K/2k signals when used in conjunction with an HDMI or HDBASE-T extender between a source and display, AES51, RS-422, IEEE802.af(PoE), IEEE802.3bt(PoE+), IEEE802.3bt(POE++)

STANDARD COMPLIANCES

- ▶ ANSI Specification: ANSI/TIA 568.2-D Category 6A
- ▶ NEC / CEC Type CMR (UL 1666) for Riser
- ▶ RoHS 3 (EU 2015/863)
- ▶ UL 444
- ▶ ASTM B-3

CERTIFICATIONS



UL and/or ETL certified, or tested by other agencies
ISO 9001: 2015, ISO 14001: 2015, OHSAS 18001

ELECTRICAL PERFORMANCE

Frequency (MHz)	Max Capacitance (nF/100m @ 1kHz)		Max DC Resistance (Ω/100m @ 68°F)		Max Delay Skew (ns/100m)		Nom Velocity of Propagation (%)		Characteristic Impedance (Ω @ 1-100MHZ)	
	5.6	9.38	45	69	100±15					
	Insertion Loss (Maximum dB/100m)	NEXT (Minimum dB/100m)	PSNEXT (Minimum dB/100m)	Return Loss (Minimum dB/100m)	PSANEXT (Minimum dB/100m)	PSAACRF (Minimum dB/100m)				
1	2.1	74.3	72.3	20.0	67.0	67.0				
4	3.8	65.3	63.3	23.0	67.0	66.2				
8	5.3	60.8	58.8	24.5	67.0	60.1				
10	5.9	59.3	57.3	25.0	67.0	58.2				
16	7.5	56.2	54.2	25.0	67.0	54.1				
20	8.4	54.8	52.8	25.0	67.0	52.2				
25	9.4	53.3	51.3	24.3	67.0	50.2				
31.25	10.5	51.9	49.9	23.6	67.0	48.3				
62.5	15.0	47.4	45.4	21.5	65.6	42.3				
100	19.1	44.3	42.3	20.1	62.5	38.2				
155	24.1	41.4	39.4	18.8	59.6	34.4				
200	27.6	39.8	37.8	18.0	58.0	32.2				
250	31.1	38.3	36.3	17.3	56.5	30.2				
300	34.3	37.1	35.1	16.8	55.3	28.7				
350	37.2	36.1	34.1	16.3	54.3	27.3				
400	40.1	35.3	33.3	15.9	53.5	26.2				
500	45.3	33.8	31.8	15.2	52.0	24.2				
550	47.7	33.2	31.2	14.9	51.4	23.4				
600	50.1	32.6	30.6	14.7	50.8	22.6				
700	54.5	31.6	29.6	14.2	49.8	21.3				

© Syston Cable Technology Corp. All Rights Reserved. Although Syston Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Syston Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory, or implied. In no event will Syston Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Syston Cable has been advised of the possibility of such damages, whether in an action under contract, negligence, or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Syston Cable products are subject to Syston Cable's standard terms and conditions contained on https://www.systoncable.com/terms-and-conditions/. Syston Cable expressly rejects any different or additional policies, preprinted or otherwise, contained or referenced in any purchase order or other documentation furnished by Buyer. Syston Cable believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Syston Cable's knowledge, information, and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.