



Power Relay F

TE Internal #: 1-1414167-0
Mini Relays, 24VDC Coil Voltage Rating, 30 - 50A Contact Current Class, Contact Arrangement 1 Form C (CO), Diode (Cathode 86), Socket, Power Relay F

[View on TE.com >](#)

Relays & Contactors > Relays > Automotive Relays > Automotive Plug-In Relays > Mini Relays



Coil Voltage Rating: 24 VDC
Contact Current Class: 30 - 50 A
Contact Arrangement: 1 Form C (CO)
Coil Special Features: Diode (Cathode 86)
Product Mount Type: Socket

Features

Configuration Features

Contact Arrangement	1 Form C (CO)
Coil Special Features	Diode (Cathode 86)

Electrical Characteristics

Contact Limiting Short-Time Current	240 A
Contact Limiting Continuous Current	60 A
Current Rating (85°C)	20 A
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Making Current	120 A
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms
Contact Limiting Breaking Current	20 A
Contact Voltage Rating	24 VDC
Contact Switching Load (Min)	1000mA @ 5VDC
Coil Power Rating DC	2100 mW
Coil Voltage Rating	24 VDC
Coil Resistance	268 Ω

Body Features

Product Weight	35 g[1.2 oz]
----------------	--------------

Contact Features



Contact Material	Silver Alloy
------------------	--------------

Termination Features

Relay Connection Type	Plug-In
Terminal Configuration	Quick Connect Terminals

Mechanical Attachment

Product Mount Type	Socket
--------------------	--------

Dimensions

Product Width	25.9 mm[1.02 in]
Product Length	25.9 mm[1.02 in]
Product Height	24.9 mm[.98 in]

Usage Conditions

Environmental Ambient Temperature (Max)	125 °C[257 °F]
---	----------------

Operation/Application

Actuating System	DC
Coil Magnetic System	Monostable

Other

Length Class (Mechanical)	25 - 30 mm
Environmental Ambient Temperature Class	105 - 125 °C
Insulation Initial Dielectric Between Coil & Contact Class	0 - 500 V
Height Class (Mechanical)	20 - 25 mm
Width Class (Mechanical)	25 - 30 mm
Contact Current Class	30 - 50 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (92.5% in Component part) Article Safe Usage Statements:



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1904045-1
V23333Z0001A007-EV-100



TE Part # 1904056-2
V23134A0007X936-EV-441



TE Part # 4-1904049-7
V23134A0007X942-EV-590



TE Part # 8-1904049-9
V23134A0007X936-EV-850



TE Part # 2383369-1
V23136A0103X151-SZ-CBOX

Also in the Series | Power Relay F




Maxi Relays(14)



Mini Relays(49)

Customers Also Bought



TE Part # 794116-1
04P .156 MNL PLUG



TE Part # 180464-5
250 FASTON,FLAG,REC.,14-17AWG, LATON




TE Part # 331467
N PIDG RING 12-10



TE Part # E46987-000
HX-SCE-1K-2.4-50-S1-4




TE Part # 170892-1
187 FASTON HSG.,REC.,NATRUAL



TE Part # 0757013001
100G0111-2.50-0



TE Part # 342452-2
5 WAY RELAY BASE.BLACK



TE Part # 1108784-1
MDL2-GR.O/U-3

Documents

Product Drawings

CAD Files

Customer View Model

ENG_CVM_1-1414167-0_S00F.3d_igs.zip

English

Customer View Model

ENG_CVM_1-1414167-0_S00F.3d_stp.zip

English

Customer View Model

ENG_CVM_1-1414167-0_S00F.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

Automotive Relay Application Notes



English

Power Relay F4, Mini ISO, Plug-In

English

Product Specifications

Definitions General Purpose Relays

English