GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: JST VHR-6N Pitch 3.96MM 6 POSITION to JST VHR-6N Pitch 3.96MM 6 POSITION, GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals: , 73mm,	
	Model No. Low voltage cable	
	Part No./Ordering No. VHR6210070M7VHR6(R)	Rev A1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT https://www.globtek.com/connectors/ STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT https://www.globtek.com/connectors/ ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification
ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at https://www.globtek.com/iso-certificates/
Prop 65 Statement:https://en.globtek.com/prop-65-statement.pdf

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (https://en.globtek.com/terms-and-conditions/).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.
Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.
A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2024
guest /05/28/2024 6:42:52 AM CLONED FROM VAR2210070M7VAR2(R)

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: JST VHR-6N Pitch 3.96MM 6 POSITION to JST VHR-6N Pitch 3.96MM 6 POSITION, GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals: , 73mm,	
	Model No. Low voltage cable	
	Part No./Ordering No. VHR6210070M7VHR6(R)	Rev A1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT https://www.globtek.com/connectors/ STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT https://www.globtek.com/connectors/ ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
A1	Remove Note: END A AND B MATES TO GTM962250PWWWVV.V-F OUTPUT CONNECTOR	QA	05/07/2024	QA
A	INITIAL RELEASE	DR	02/09/2019	QA

Cordset Information:
CordsetColor:
Cord Length (mm):73

NOTES:

PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2024
guest /05/28/2024 6:42:52 AM CLONED FROM VAR2210070M7VAR2(R)

GlobTek, Inc.
www.globtek.com
186 Veterans Drive,
Northvale, NJ 07647
Tel. (201) 784-1000
Fax (201) 784-0111

Drawing Title: JST VHR-6N Pitch 3.96MM 6 POSITION to JST VHR-6N Pitch 3.96MM 6 POSITION, GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals: , 73mm,	
Model No. Low voltage cable	
Part No./Ordering No. VHR6210070M7VHR6(R)	Rev A1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT https://www.globtek.com/connectors/ STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT https://www.globtek.com/connectors/ ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

END A



END B




PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2024
guest /05/28/2024 6:42:52 AM CLONED FROM VAR2210070M7VAR2(R)

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: JST VHR-6N Pitch 3.96MM 6 POSITION to JST VHR-6N Pitch 3.96MM 6 POSITION, GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals: , 73mm,	
	Model No. Low voltage cable	
	Part No./Ordering No. VHR6210070M7VHR6(R)	Rev A1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT https://www.globtek.com/connectors/ STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT https://www.globtek.com/connectors/ ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

CABLE IMAGE



PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2024
guest /05/28/2024 6:42:52 AM CLONED FROM VAR2210070M7VAR2(R)

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: JST VHR-6N Pitch 3.96MM 6 POSITION to JST VHR-6N Pitch 3.96MM 6 POSITION, GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals: , 73mm,	
	Model No. Low voltage cable	
	Part No./Ordering No. VHR6210070M7VHR6(R)	Rev A1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT https://www.globtek.com/connectors/ STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT https://www.globtek.com/connectors/ ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

End A	Cable	End B
Code:VHR6	Code:6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE	Code:VHR6
Description:JST VHR-6N Pitch 3.96MM 6 POSITION	Description:GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals:	Description:JST VHR-6N Pitch 3.96MM 6 POSITION
Rating (V):250	Color:GlobTek Black	Rating (V):250
Rating (A):	Wire Gauge(AWG):22	Rating (A):
Gender:Female	Cond:6	Gender:Female
Overmolded:No	Type:UL1007	Overmolded:No
	Temperature:80° C	
	Amps:3	
	Volts:300	
	OD:1.6	
	ConductorsColors:3 BLACK, 3 WHITE	

Overall cable rating:

Plug Approvals	Cable Approvals	Connector Approvals
	UL RECOGNIZED	

AGENCY ONLINE DOCUMENTS	http://en.globtek.com/cordsets/
RoHS/RoHS3 Declaration	https://www.globtek.com/pdf/rohs_cert/01t0c0000096zrrAAA
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf
Prop 65 Statement	https://en.globtek.com/prop-65-statement.pdf
CE.UKCA.Cord	https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01t0c0000096zrr

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.

PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2024
guest /05/28/2024 6:42:52 AM CLONED FROM VAR2210070M7VAR2(R)

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: JST VHR-6N Pitch 3.96MM 6 POSITION to JST VHR-6N Pitch 3.96MM 6 POSITION, GT Cable #6*UL1007 22AWG WIRE, 3 BLACK, 3 WHITE: 22 / 6 Conductors, 1.6mm OD, UL1007, 80 Deg.C, 300V, 3 BLACK, 3 WHITE, Approvals: , 73mm,	
	Model No. Low voltage cable	
	Part No./Ordering No. VHR6210070M7VHR6(R)	Rev A1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT https://www.globtek.com/connectors/ STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT https://www.globtek.com/connectors/ ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:NO HANK
Description:NO HANK, BULK PACKED
Image:

Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):

PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2024

guest /05/28/2024 6:42:52 AM CLONED FROM VAR2210070M7VAR2(R)