

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing



1082566

<https://www.phoenixcontact.com/us/products/1082566>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B6, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 2, lateral, 2x M40, height: 74.8 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1082566
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 599 (C-2-2019)
GTIN	4055626816135
Weight per piece (including packing)	233.9 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85389099
Country of origin	CN

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing



1082566

<https://www.phoenixcontact.com/us/products/1082566>

Technical data


Notes

General	For contact inserts HC-B6, BB10, DD24, M Tall housings for extra large wiring space
---------	---

Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B6
No. of cable outlets	2
Type of the screw connection	2x M40
Type	Tall design
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	52 mm
Height	74.8 mm
Length	84 mm
Hole diameter	5.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	2x M40
Locking type	Latch

Connection data

Tightening torque	2 Nm ... 3 Nm (for M5 mounting screws on the surface-mount housing)
-------------------	---

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing



1082566

<https://www.phoenixcontact.com/us/products/1082566>

Mounting

Assembly note	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
---------------	---

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing




1082566

<https://www.phoenixcontact.com/us/products/1082566>

Drawings

Dimensional drawing



Dimensional drawing

1082566

<https://www.phoenixcontact.com/us/products/1082566>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1082566>



DNV
Approval ID: TAE000037S



cUL Recognized
Approval ID: E255026



UL Recognized
Approval ID: E255026



EAC
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing



1082566

<https://www.phoenixcontact.com/us/products/1082566>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing



1082566

<https://www.phoenixcontact.com/us/products/1082566>

Accessories

G-INS-M40-M68N-NNES-S - Cable gland

1411167

<https://www.phoenixcontact.com/us/products/1411167>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 19 mm ... 28 mm, shielding: no, connecting thread: M40 x 1.5, color: silver, with O-ring

G-INSEC-M40-M68N-NCRS-S - Cable gland

1411192

<https://www.phoenixcontact.com/us/products/1411192>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 19 mm ... 27 mm, shielding: yes, connecting thread: M40 x 1.5, color: silver, with O-ring

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



HC-STA-B06-SL-PLBK - Housing brackets

1412591

<https://www.phoenixcontact.com/us/products/1412591>

Single locking latch for B6 housing, HC-EVO....AL and HC-STA....AL



HC-B06-SP-CBK - Profile gasket

1411477

<https://www.phoenixcontact.com/us/products/1411477>

Profile gasket for HEAVYCON EVO supporting base element type B6, conductive



HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



HC-B06-BC-HI-PLBK - Protective cover

1407692

<https://www.phoenixcontact.com/us/products/1407692>

Protective cover B6, for single locking latch, protective cover material: PC, height: 19 mm, seal: no



HC-B06-BCFS-P-BK - Protective cover

1346524

<https://www.phoenixcontact.com/us/products/1346524>

Protective cover B6, for single locking latch, protective cover material: PC, height: 26.3 mm, seal: no



HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



HC-STA-B06-DC-PL - Protective cover

1421100

<https://www.phoenixcontact.com/us/products/1421100>

Protective cover, design: B6



WP-G HF IP66 M40 BK - Screw connection

3240901

<https://www.phoenixcontact.com/us/products/3240901>

Cable gland, metric thread, IP66 protection, straight



HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



WP-G HF IP69K M40 BK - Screw connection

3240887

<https://www.phoenixcontact.com/us/products/3240887>

Cable gland, metric thread, IP68/69k protection, straight



WP-GA HF IP66 M40 BK - Screw connection

3240929

<https://www.phoenixcontact.com/us/products/3240929>

Cable gland, metric thread, IP66 protection, angled



HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



WP-GA HF IP69K M40 BK - Screw connection

3240915

<https://www.phoenixcontact.com/us/products/3240915>

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M40 BK - Screw connection

3240957

<https://www.phoenixcontact.com/us/products/3240957>

Cable gland, metric thread, IP66 protection, with strain relief



HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



WP-GR HF IP69K M40 BK - Screw connection

3240943

<https://www.phoenixcontact.com/us/products/3240943>



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M40 - Screw connection

3241001

<https://www.phoenixcontact.com/us/products/3241001>



Cable gland made from PP with metric thread, IP65 protection

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing



1082566

<https://www.phoenixcontact.com/us/products/1082566>

WP-GT PP HF M40 - Screw connection

3241015

<https://www.phoenixcontact.com/us/products/3241015>



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M40 - Screw connection

3241050

<https://www.phoenixcontact.com/us/products/3241050>



Cable gland made from brass with metric thread, IP40 protection

HC-STA-B06-SHWS-2SSM40-ELC-AL - Housing

1082566

<https://www.phoenixcontact.com/us/products/1082566>



WP-GT BRASS M40 - Screw connection

3241036

<https://www.phoenixcontact.com/us/products/3241036>

Cable gland made from brass with metric thread, rotatable, IP40 protection



WP-G BRASS IP65 M40 - Screw connection

3241064

<https://www.phoenixcontact.com/us/products/3241064>

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com