

3000755

<https://www.phoenixcontact.com/us/products/3000755>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Electronic circuit breaker, on/off control input, nominal current: 2 A

Commercial data

Item number	3000755
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CL04
Product key	CLA131
GTIN	4046356708470
Weight per piece (including packing)	69.5 g
Weight per piece (excluding packing)	69.5 g
Customs tariff number	85362010
Country of origin	DE

EC 1 12DC/2A S-C - Electronic circuit breaker



3000755

<https://www.phoenixcontact.com/us/products/3000755>

Technical data

Product properties

Product type	Device circuit breakers
Product family	EC-E
Type	DIN rail module, one-piece
Number of positions	1

Electrical properties

Maximum load current	2 A (100% duty cycle, 40°C)
	2 A (100% duty cycle, 50°C)
Service life electrical	10000

General

Fuse	electronic
------	------------

Connection data

Maximum load current	2 A (100% duty cycle, 40°C)
	2 A (100% duty cycle, 50°C)

Line+ / LOAD+ /0V

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Conductor cross section rigid	0.5 mm² ... 10 mm²
Conductor cross section flexible	0.5 mm² ... 10 mm²
2 conductors with same cross section, solid	0.5 mm² ... 4 mm²
2 conductors with same cross section, flexible	0.5 mm² ... 4 mm²
Nominal current	2 A
Nominal voltage	12 V DC

Signal connections

Screw thread	M3
Tightening torque	0.5 ... 0.6 Nm
Conductor cross section flexible	0.25 mm² ... 2.5 mm²

Dimensions

Width	12.5 mm
Height	80 mm

Material specifications

Color	black (RAL 9005)
-------	------------------

Environmental and real-life conditions

Ambient conditions

EC 1 12DC/2A S-C - Electronic circuit breaker



3000755

<https://www.phoenixcontact.com/us/products/3000755>

Ambient temperature (operation)	-20 °C ... 60 °C (ordinary locations)
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

EC 1 12DC/2A S-C - Electronic circuit breaker



3000755

<https://www.phoenixcontact.com/us/products/3000755>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3000755>



cUL Recognized
Approval ID: FILE E 140324



UL Recognized
Approval ID: FILE E 317172



DNV GL
Approval ID: TAE00002HC



UL Recognized
Approval ID: FILE E 140324



UL Listed
Approval ID: FILE E 140324



cUL Listed
Approval ID: FILE E 140324



UL Recognized
Approval ID: FILE E 324415

cULus Listed

EC 1 12DC/2A S-C - Electronic circuit breaker



3000755

<https://www.phoenixcontact.com/us/products/3000755>

Classifications

ECLASS

ECLASS-11.0	27141116
ECLASS-12.0	27141116
ECLASS-13.0	27140401

ETIM

ETIM 9.0	EC000899
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-25
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	8ab8cb44-56d7-4069-abc8-ca5c3a157532

EC 1 12DC/2A S-C - Electronic circuit breaker

3000755

<https://www.phoenixcontact.com/us/products/3000755>



Accessories

FBST 500 TMC-N GY - Continuous plug-in bridge

0901028

<https://www.phoenixcontact.com/us/products/0901028>



Continuous plug-in bridge, mounting type: Plug-in mounting

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com