



MTA 156

TE Internal #: 3-644615-9

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 9

Position, 3.96 mm [.156 in] Centerline, Printed Circuit Board, UL 94V-0, MTA 156

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **9**

Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Header Type	Partially Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Keying & Polarized Position Locations	3&4, 6&7
Number of Positions	9
PCB Mount Orientation	Vertical
Number of Power Positions	9
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Mating Post Length	11.43 mm[.45 in]
PCB Contact Termination Area Plating Material Thickness	2.54 µm[100 µin]
Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	7 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	3.81 µm[150 µin]

Termination Features

Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment Type	Peg
Strain Relief	Without
Mating Alignment Type	Backwall Interruptions Between Posts
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
Panel Mount Feature	Without
PCB Mount Retention	With
PCB Mount Retention Type	Tab
Mating Retention Type	Polarized Lock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	Polyester - GF

Dimensions

--



Connector Height	13.84 mm[.545 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
Product Length	35.53 mm[1.399 in]

Usage Conditions

Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

CSA Rating	Certified, LR 7189
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C






Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Part # CAT-103156-WBHSM Receptacle Housing: Wire-to-Board, with Mating Alignment, SL156</p>	 <p>TE Part # 640251-9 09P SL156 HSG W/O LCK RAMP</p>	 <p>TE Part # 3-643817-9 09P MTA156 CONN ASSY 18AWG LF</p>	 <p>TE Part # 3-643818-9 09P MTA156 CONN ASSY 20AWG YEL</p>
 <p>TE Part # 3-640426-9 09P MTA156 CONN ASSY 18AWG ORA</p>	 <p>TE Part # 3-640428-9 09P MTA156 CONN ASSY 22AWG RED</p>	 <p>TE Part # 3-640599-9 09P MTA156 CONN ASSY 18AWG ORA</p>	 <p>TE Part # 3-640427-9 09P MTA156 CONN ASSY 20AWG YEL ORA</p>
 <p>TE Part # 3-643819-9 09P MTA156 CONN ASSY 22AWG RED</p>	 <p>TE Part # 3-640429-9 09P MTA156 CONN ASSY 24AWG WHT</p>	 <p>TE Part # 640551-9 09P MTA156 COVER</p>	 <p>TE Part # 643067-9 09P MTA156 MOLDED COVER</p>
 <p>TE Part # 643071-9 09P MTA156 FD-THRU COVER</p>	 <p>TE Part # 3-640432-9 09P MTA156 CONN ASSY 20AWG YEL</p>	 <p>TE Part # 3-640433-9 09P MTA156 CONN ASSY 22AWG RED</p>	 <p>TE Part # 640643-9 09P MTA156 COVER F/T</p>



TE Part # 3-640431-9
09P MTA156 CONN ASSY 18AWG
ORA

TE Part # 3-1744319-9
09P MTA156 POL HDR ASSY LF OMIT
6&8

TE Part # 3-643820-9
09P MTA156 CONN ASSY 24AWG LF

TE Part # 3-640600-9
09P MTA156 CONN ASSY 20AWG LF

Also in the Series | MTA 156

Connector Caps & Covers(89)

Connector Contacts(4)

Connector Hardware(2)

Insertion & Extraction Tools(1)

PCB Headers & Receptacles(314)

Rectangular Power Connectors(691)

Standard Rectangular Connectors(336)

Customers Also Bought

TE Part # 2-5332070-3
SOCKET,MIN-SPR SN-AU SER-4

TE Part # 1558661-6
T9GV1L14-22

TE Part # 2-1825027-0
FSMRA7JH04=R/A,TACT PB SW,160G

TE Part # 643410-1
08P UMNL PIN HDR ASSY POL 94VO

TE Part # 8-1393243-0
RT425005

TE Part # 647609-8
08P MTA100 HDR ASSY F/L

TE Part # 1546209-5
TERMI-BLOCK HEADER ASSY90 5P.

TE Part # 1-6450520-8
MBXL R/A W/GUIDE 4P+8S+6P



Documents

Product Drawings

09P MTA156 POL HDR ASSY LF

English

CAD Files

Customer View Model

ENG_CVM_3-644615-9_J.2d_dxf.zip

English

3D PDF

English

Customer View Model

ENG_CVM_3-644615-9_J.3d_igs.zip

English

Customer View Model

ENG_CVM_3-644615-9_J.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-644615-9_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-644615-9_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-644615-9_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

CSA Certificate

English