# T4082102003-000 ACTIVE



#### M8 Connector

TE Internal #: T4082102003-000

Standard Circular Connectors, Cable-to-Cable, 3 Position, Sealable,

Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse

Gender, M8 Connector

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 3

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

### **Features**

### **Product Type Features**

Assembled al Connector
al Connector
al Connector
tor Assembly
o-Cable
Cable
t

No

Factory Installed Backshell



Keying	A
Number of Positions	3
Number of Power Positions	0
Number of Signal Positions	3
Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	60 VAC
Body Features	
Peripheral Seal Material	Silicone
Environmental Protection	IP67
O-Ring Material	Silicone
Environmental Protection Type	Sealed
Shell Plating Material	Unplated
Shell Base Material	Plastic
Circular Connector Insulation Material Type	Polyamide 66 GF25
Hermetically Sealed	Yes
Contact Features	
Contact Current Rating (Max)	3 A
Contact Current Rating (Max) Reverse Gender	3 A Yes
Reverse Gender	Yes
Reverse Gender  Circular Connector Contact Type	Yes
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment	Yes Pin
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type	Yes Pin  Cable Mount (Free-Hanging)
Reverse Gender Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type  Polarization Code	Yes Pin  Cable Mount (Free-Hanging)  A
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type  Polarization Code  Mating Alignment Type	Yes Pin  Cable Mount (Free-Hanging)  A
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type  Polarization Code  Mating Alignment Type  Usage Conditions	Yes Pin  Cable Mount (Free-Hanging)  A  Keyed
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type  Polarization Code  Mating Alignment Type  Usage Conditions  IP Dust Sealing Level	Yes Pin  Cable Mount (Free-Hanging)  A  Keyed
Reverse Gender Circular Connector Contact Type  Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type  Usage Conditions IP Dust Sealing Level IP Water Sealing Level	Yes Pin  Cable Mount (Free-Hanging)  A  Keyed  6  IP67
Reverse Gender Circular Connector Contact Type  Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type  Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range	Yes Pin  Cable Mount (Free-Hanging)  A  Keyed  6  IP67
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type  Polarization Code  Mating Alignment Type  Usage Conditions  IP Dust Sealing Level  IP Water Sealing Level  Operating Temperature Range  Operation/Application	Yes Pin  Cable Mount (Free-Hanging)  A  Keyed  6  IP67  -40 - 85 °C[-40 - 185 °F]
Reverse Gender  Circular Connector Contact Type  Mechanical Attachment  Connector Mounting Type  Polarization Code  Mating Alignment Type  Usage Conditions  IP Dust Sealing Level  IP Water Sealing Level  Operating Temperature Range  Operation/Application  Durability Rating	Yes Pin  Cable Mount (Free-Hanging)  A  Keyed  6  IP67  -40 - 85 °C[-40 - 185 °F]  100 Cycles



### **Industry Standards**

UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	1

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (4% in Pb-Alloy in Copper) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Also in the Series | M8 Connector









Connector Hardware(4)

M8/M12 Cable Assemblies(147)

Standard Circular Connectors(106)

# Customers Also Bought




TE Part # T4111002041-000 M12,MALE,STRAIGHT,A CODE,4P, PG9,GOLD



TE Part # T4011008031-000 M8, SCREW, MALE, S, UNSHIELD, 3P, GOLD



TE Part # T4062113003-001 RPC-M8-3MS-0.5SH-M8-3FS-PVC



TE Part # 1804030-1 **EXTRACTION TOOL ASSY** 



TE Part # 350779-4 04P UMNL PLUG HSG UL94VO




TE Part # 1-406541-5 MJ,INV,1X1,0PNL G,.100"ST,SN



TE Part # 9-2176087-4 RP 1J 0.166W 649R 0.1% 25PPM 1K RL









### **Documents**

### **Product Drawings**

M8 T DISTRIBUTOR MALE 3POS

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_T4082102003-000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_T4082102003-000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_T4082102003-000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

## Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

### **Product Specifications**

**Application Specification** 

English

**Application Specification** 

English

## Agency Approvals

UL

English