

Part Number: 1727040021

Product Description: FCT Mixed Layout D-Sub Connector, Male, Straight, Solder Cup, Gold over Nickel Phosphorus Plating, Tin-plated Shell with Dimples, 21 Circuits Max, 20 Signal Contacts Loaded, Green Insulator

Series Number: 172704 **Status:** Active

Product Category: D-Sub Connectors **Engineering Number:** FM21W1PA-K120

Documents & Resources

Drawings

Drawing 1727040021_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | D-Sub Connectors |
| Series | 172704 |
| Description | FCT Mixed Layout D-Sub Connector, Male, Straight, Solder Cup, Gold over Nickel Phosphorus Plating, Tin-plated Shell with Dimples, 21 Circuits Max, 20 Signal Contacts Loaded, Green Insulator |
| IP Rating | IP20 |
| Magnetic | Yes |
| Product Family | FCT D-Sub Connectors |
| Product Name | FCT Products |
| Туре | Mixed Layout |
| UPC | 889056019323 |

Electrical

| Current - Maximum per Contact | 7.5A |
|-------------------------------|------|
| Shielded | Yes |

Physical

| Circuits (Loaded) | 20 |
|--------------------------------|--------------|
| Circuits (maximum) | 21 |
| Color - Resin | Green |
| Durability (mating cycles max) | 500 |
| Gender | Male |
| Material - Contact | Copper Alloy |
| Material - Resin | PBT |
| Material - Shell | Steel |
| Net Weight | 10.100/g |
| Number of Rows | 2 |
| Orientation | Straight |
| Packaging Type | Carton |
| Panel Mount | Rear |
| Panel Mount Method | Flange |

| PCB Locator | No |
|-------------------------------|-----------------------------|
| PCB Retention | None |
| Pitch - Mating Interface | 2.84mm |
| Pitch - Termination Interface | 2.84mm |
| Plating - Contact | Gold over Nickel Phosphorus |
| Plating - Shell | Tin |
| Polarized to Mating Part | Yes |
| Ports | 1 |
| Temperature Range - Operating | -55° to +130°C |
| Termination Style | Solder Cup |
| Waterproof / Dustproof | No |
| Waterproof / Dustproof Type | IP20 |
| Wire Size (AWG) | 20 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|-------------|---|
| Mates With | FCT Mixed Layout D-Sub, Size 3, 21W1, Socket |

Use with Part(s)

| Description | Part Number |
|-------------|---|
| Use With | FCT Coaxial, High Power, High Voltage, or Pneumatic Contacts |

This document was generated on Jul 18, 2024