# VIP-2/PT/HD15SUB/M - Interface module

2904268

https://www.phoenixcontact.com/us/products/2904268

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with push-in connections and high density D-SUB miniature pin-strip, for mounting on NS 35 rails, no. of pos.: 15

## Commercial data

| | |
|---|---|
| Item number | 2904268 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | C423 |
| Product key | CK2122 |
| Catalog page | Page 591 (C-7-2015) |
| GTIN | 4046356814775 |
| Weight per piece (including packing) | 119.5 g |
| Weight per piece (excluding packing) | 108.2 g |
| Customs tariff number | 85366990 |
| Country of origin | US |

## Technical data

### Product properties

| | |
|---|---|
| Product type | Interface module |
| Product family | VARIOFACE Professional |
| Number of positions | 15 |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | II |
| Pollution degree | 2 |

### Electrical properties

| | |
|---|---|
| Nominal voltage $U_N$ | 25 V AC |
| | 60 V DC |
| Max. current carrying capacity per branch | 1 A |
| Rated surge voltage | 1.2 kV |

### Connection data

Connection 1 (control level)

| | |
|---|---|
| Connection method | High density D-SUB pin strip |
| Screw thread | UNC 4-40 |
| Number of connections | 1 |
| Number of positions | 15 |

Connection 2 (field level)

| | |
|---|---|
| Connection in acc. with standard | IEC / EN |
| Connection method | Push-in connection |
| Stripping length | 8 mm |
| Number of positions | 16 |
| Conductor cross section rigid | 0.14 mm² ... 2.5 mm² |
| Conductor cross section flexible | 0.14 mm² ... 2.5 mm² |
| Conductor cross section AWG | 26 ... 14 |

### Signaling

| | |
|---|---|
| Status display | No |
| Status display present | No |

### Dimensions

Item dimensions

| | |
|---|---|
| Width | 46.9 mm |
| Height | 72.1 mm |
| Depth | 46.6 mm |

### Material specifications

| | |
|---|---|
| Color | gray (RAL 7042) |
| Housing insulation material | Polyamide 6.6 green |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

## Standards and regulations

| | |
|---|---|
| Standards/regulations | EN 50178 |

## Mounting


| | |
|---|---|
| Mounting type | DIN rail mounting |
| Mounting position | any |

## Notes


| | |
|---|---|
| Notes on operation | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |

## Drawings

Circuit diagram




Dimensional drawing



## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2904268

**CSA**
Approval ID: 2122203

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 105 V | 1 A | 26 - 14 | - |

**cUL Recognized**
Approval ID: FILE E 238705

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 125 V | 1 A | 26 - 14 | - |

**UL Recognized**
Approval ID: FILE E 238705

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 125 V | 1 A | 26 - 14 | - |

**CSAus**
Approval ID: 2122203

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 105 V | 1 A | 28 - 14 | - |

**cULus Recognized**

**cCSAus**

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27141152 |
| ECLASS-13.0 | 27141152 |
| ECLASS-12.0 | 27141152 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC002780 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121400 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 6(c) |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 2a417660-2a69-45b8-ab63-251f0eb4218c |


Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com