NPN - 2N6515, 2N6517; PNP - 2N6520

High Voltage Transistors


NPN and PNP

ON Semiconductor®

http://onsemi.com

Features

- Voltage and Current are Negative for PNP Transistors
- These are Pb−Free Devices*



MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage 2N6515 2N6517, 2N6520	V_{CEO}	 250 350	Vdc
Collector − Base Voltage 2N6515 2N6517, 2N6520	V_{CBO}	 250 350	Vdc
Emitter − Base Voltage 2N6515, 2N6517 2N6520	V_{EBO}	 6.0 5.0	Vdc
Base Current	I_B	250	mAdc
Collector Current − Continuous	I_C	500	mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0	mW mW/°C
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	1.5 12	W mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−55 to +150	°C


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	200	°C/W
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	83.3	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


TO−92
CASE 29
STYLE 1



STRAIGHT LEAD
BULK PACK

BENT LEAD
TAPE & REEL
AMMO PACK

MARKING DIAGRAM



xx = 15, 17, or 20
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (Note 1)		$V_{(BR)CEO}$			Vdc
(I_C = 1.0 mAdc, I_B = 0)	2N6515		250	−	
	2N6517, 2N6520		350	−	
Collector−Base Breakdown Voltage		$V_{(BR)CBO}$			Vdc
(I_C = 100 μAdc, I_E = 0)	2N6515		250	−	
	2N6517, 2N6520		350	−	
Emitter−Base Breakdown Voltage		$V_{(BR)EBO}$			Vdc
(I_E = 10 μAdc, I_C = 0)	2N6515, 2N6517		6.0	−	
	2N6520		5.0	−	
Collector Cutoff Current		I_{CBO}			nAdc
(V_{CB} = 150 Vdc, I_E = 0)	2N6515		−	50	
(V_{CB} = 250 Vdc, I_E = 0)	2N6517, 2N6520		−	50	
Emitter Cutoff Current		I_{EBO}			nAdc
(V_{EB} = 5.0 Vdc, I_C = 0)	2N6515, 2N6517		−	50	
(V_{EB} = 4.0 Vdc, I_C = 0)	2N6520		−	50	
ON CHARACTERISTICS (Note 1)					
DC Current Gain		h_{FE}			−
(I_C = 1.0 mAdc, V_{CE} = 10 Vdc)	2N6515		35	−	
	2N6517, 2N6520		20	−	
(I_C = 10 mAdc, V_{CE} = 10 Vdc)	2N6515		50	−	
	2N6517, 2N6520		30	−	
(I_C = 30 mAdc, V_{CE} = 10 Vdc)	2N6515		50	300	
	2N6517, 2N6520		30	200	
(I_C = 50 mAdc, V_{CE} = 10 Vdc)	2N6515		45	220	
	2N6517, 2N6520		20	200	
(I_C = 100 mAdc, V_{CE} = 10 Vdc)	2N6515		25	−	
	2N6517, 2N6520		15	−	
Collector−Emitter Saturation Voltage		$V_{CE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)			−	0.30	
(I_C = 20 mAdc, I_B = 2.0 mAdc)			−	0.35	
(I_C = 30 mAdc, I_B = 3.0 mAdc)			−	0.50	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			−	1.0	
Base−Emitter Saturation Voltage		$V_{BE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)			−	0.75	
(I_C = 20 mAdc, I_B = 2.0 mAdc)			−	0.85	
(I_C = 30 mAdc, I_B = 3.0 mAdc)			−	0.90	
Base−Emitter On Voltage		$V_{BE(on)}$	−	2.0	Vdc
(I_C = 100 mAdc, V_{CE} = 10 Vdc)					
SMALL−SIGNAL CHARACTERISTICS					
Current−Gain − Bandwidth Product (Note 1)		f_T	40	200	MHz
(I_C = 10 mAdc, V_{CE} = 20 Vdc, f = 20 MHz)					
Collector−Base Capacitance		C_{cb}	−	6.0	pF
(V_{CB} = 20 Vdc, I_E = 0, f = 1.0 MHz)					
Emitter−Base Capacitance		C_{eb}			pF
(V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	2N6515, 2N6517		−	80	
	2N6520		−	100	
SWITCHING CHARACTERISTICS					
Turn−On Time		t_{on}	−	200	μs
(V_{CC} = 100 Vdc, $V_{BE(off)}$ = 2.0 Vdc, I_C = 50 mAdc, I_{B1} = 10 mAdc)					
Turn−Off Time		t_{off}	−	3.5	μs
(V_{CC} = 100 Vdc, I_C = 50 mAdc, I_{B1} = I_{B2} = 10 mAdc)					

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.




Figure 1. DC Current Gain
NPN 2N6515




Figure 2. DC Current Gain
NPN 2N6517




Figure 3. DC Current Gain
PNP 2N6520




Figure 4. Current−Gain − Bandwidth Product
NPN 2N6515, 2N6517




Figure 5. Current−Gain − Bandwidth Product
PNP 2N6520




Figure 6. “On” Voltages
NPN 2N6515, 2N6517




Figure 7. “On” Voltages
PNP 2N6520




Figure 8. Temperature Coefficients
NPN 2N6515, 2N6517




Figure 9. Temperature Coefficients
PNP 2N6520




Figure 10. Capacitance
NPN 2N6515, 2N6517




Figure 11. Capacitance
PNP 2N6520




Figure 12. Turn−On Time
NPN 2N6515, 2N6517




Figure 13. Turn−On Time
PNP 2N6520




Figure 14. Turn−Off Time
NPN 2N6515, 2N6517




Figure 15. Turn−Off Time
PNP 2N6520




Figure 16. Switching Time Test Circuit




Figure 17. Thermal Response





Figure 18. Active Region Safe Operating Area



Design Note: Use of Transient Thermal Resistance Data

ORDERING INFORMATION

Device	Package	Shipping†
2N6515RLRMG	TO−92 (Pb−Free)	2000 Ammo Pack
2N6517G	TO−92 (Pb−Free)	5000 Unit / Bulk
2N6517RLRPG	TO−92 (Pb−Free)	2000 Ammo Pack
2N6520RLRAG	TO−92 (Pb−Free)	2000 Tape & Reel


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

ON Semiconductor®


TO–92 (TO–226)
CASE 29–11
ISSUE AM

DATE 09 MAR 2007




STRAIGHT LEAD
BULK PACK

BENT LEAD
TAPE & REEL
AMMO PACK




STRAIGHT LEAD
BULK PACK




SECTION X–X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---



BENT LEAD
TAPE & REEL
AMMO PACK



SECTION X–X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	MILLIMETERS	
DIM	MIN	MAX
A	4.45	5.20
B	4.32	5.33
C	3.18	4.19
D	0.40	0.54
G	2.40	2.80
J	0.39	0.50
K	12.70	---
N	2.04	2.66
P	1.50	4.00
R	2.93	---
V	3.43	---

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42022B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
STATUS:	**ON SEMICONDUCTOR STANDARD**	
NEW STANDARD:		
DESCRIPTION:	**TO–92 (TO–226)**	**PAGE 1 OF 3**

TO−92 (TO−226)
CASE 29−11
ISSUE AM

DATE 09 MAR 2007

STYLE 1:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 2:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. DRAIN
2. SOURCE
3. GATE

STYLE 6:
PIN 1. GATE
2. SOURCE & SUBSTRATE
3. DRAIN

STYLE 7:
PIN 1. SOURCE
2. DRAIN
3. GATE

STYLE 8:
PIN 1. DRAIN
2. GATE
3. SOURCE & SUBSTRATE

STYLE 9:
PIN 1. BASE 1
2. EMITTER
3. BASE 2

STYLE 10:
PIN 1. CATHODE
2. GATE
3. ANODE

STYLE 11:
PIN 1. ANODE
2. CATHODE & ANODE
3. CATHODE

STYLE 12:
PIN 1. MAIN TERMINAL 1
2. GATE
3. MAIN TERMINAL 2

STYLE 13:
PIN 1. ANODE 1
2. GATE
3. CATHODE 2

STYLE 14:
PIN 1. EMITTER
2. COLLECTOR
3. BASE

STYLE 15:
PIN 1. ANODE 1
2. CATHODE
3. ANODE 2

STYLE 16:
PIN 1. ANODE
2. GATE
3. CATHODE

STYLE 17:
PIN 1. COLLECTOR
2. BASE
3. EMITTER

STYLE 18:
PIN 1. ANODE
2. CATHODE
3. NOT CONNECTED

STYLE 19:
PIN 1. GATE
2. ANODE
3. CATHODE

STYLE 20:
PIN 1. NOT CONNECTED
2. CATHODE
3. ANODE

STYLE 21:
PIN 1. COLLECTOR
2. EMITTER
3. BASE

STYLE 22:
PIN 1. SOURCE
2. GATE
3. DRAIN

STYLE 23:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 24:
PIN 1. EMITTER
2. COLLECTOR/ANODE
3. CATHODE

STYLE 25:
PIN 1. MT 1
2. GATE
3. MT 2

STYLE 26:
PIN 1. V_{CC}
2. GROUND 2
3. OUTPUT

STYLE 27:
PIN 1. MT
2. SUBSTRATE
3. MT

STYLE 28:
PIN 1. CATHODE
2. ANODE
3. GATE

STYLE 29:
PIN 1. NOT CONNECTED
2. ANODE
3. CATHODE

STYLE 30:
PIN 1. DRAIN
2. GATE
3. SOURCE

STYLE 31:
PIN 1. GATE
2. DRAIN
3. SOURCE

STYLE 32:
PIN 1. BASE
2. COLLECTOR
3. EMITTER

STYLE 33:
PIN 1. RETURN
2. INPUT
3. OUTPUT

STYLE 34:
PIN 1. INPUT
2. GROUND
3. LOGIC

STYLE 35:
PIN 1. GATE
2. COLLECTOR
3. EMITTER

ISSUE	REVISION	DATE
AM	ADDED BENT−LEAD TAPE & REEL VERSION. REQ. BY J. SUPINA.	09 MAR 2007

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales