




Positive Lock | Positive Lock 250

TE Internal #: 341299-2

Quick Disconnects, Receptacle, 20 - 15 AWG Wire Size, .51 - 1.65 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, Positive Lock 250

[View on TE.com >](#)

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 - 1.65 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Extraction Force	7 - 100 Newton
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.36 mm[.014 in]
Product Length	21.67 mm[.853 in]
Compatible Insulation Diameter Range	2.1 - 2.9 mm[.083 - .114 in]
Wire Size	.51 - 1.65 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	5000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Part # 63239-1 POSITIVE LOCK 250 REC 12-10 AWG TPBR</p>	 <p>TE Part # 170329-1 250 PL MKII REC. 15-10AWG PTBR</p>	 <p>TE Part # 1217092-1 PL 250 TERMINAL RECEPTACLE 16-12 AWG BR</p>	 <p>TE Part # 172765-1 PL 250 FLAG REC 14-12 0.40 X 49.2 PTBR</p>
 <p>TE Part # 1742354-1 PL 250 REC 16-18AWG PTBR</p>	 <p>TE Part # 1217092-2 PL 250 TERMINAL REC 16-12 AWG TPBR</p>	 <p>TE Part # 172761-1 PL 250 FLAG REC 18-22 0.40 X 49.2 PTBR</p>	 <p>TE Part # 190679-2 POSILOK T'P</p>
 <p>TE Part # 2238155-1 POS LOCK 250 Rec, MKII, 18-14 TPBR</p>	 <p>TE Part # 281384-2 POS LOCK RCPT CTC SNPL</p>	 <p>TE Part # 341299-1 POSILOK RECPT MK II .250</p>	

Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(192)



Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(4)



Quick Disconnects(186)


Customers Also Bought



TE Part # 350570-1
UMNL SOK 24-18 PTPBR



TE Part # 62191-1
110 FASTON REC 20-16 AWG TPBR



TE Part # 104479-8
SHORT POINT CONT PLTD SN




TE Part # 62896-1
MAG-MATE POKE-IN TAB 018 PTPBR




TE Part # 640271-3
RING 22-18 AWG TPST



TE Part # 1318620-2
TH/.025 CONNECTOR SYSTEM,
HOUSING



TE Part # 1674742-1
025 TH TAB CONTACT



TE Part # 154718-7
PL 250 REC TERMINAL 18-14 AWG
PTPPB



TE Part # 62638-1
RING TONGUE 22-20 AWG TPBR

Documents



Product Drawings

PL 250 REC TERMINAL 20-15 AWG PTPB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_341299-2_V.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_341299-2_V.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_341299-2_V.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.