



Energy & Power > Power Cable Accessories > Power Cable Terminations > Cold Shrink Terminations



Power Cable Termination Product Availability: **Americas**

Installation Instruction: **English**

Power Cable Termination Technology: **Cold Applied, Cold Shrink**

Power Cable Termination Voltage Class: **≤ 15 kV**

Cable Shield Style: **Copper Tape**

[All Cold Shrink Terminations \(171\)](#)

Features

Product Type Features

Compression Lug Included (Shield)	No
Product Family	CST
Shelf Life	3 Years
Compression Lug Included (Conductor)	No
Power Cable Termination Technology	Cold Applied, Cold Shrink
Cable Shield Style	Copper Tape
Insulation	XLPE/EPR
Sheds per Phase	4
Mechanical Connectors Included	No
Mechanical Lug Included (Shield)	No

Configuration Features

Number of Cores	1
-----------------	---

Electrical Characteristics

Power Cable Termination Voltage Class	≤ 15 kV
---------------------------------------	---------

Dimensions

	2 - 4/0 AWG/kcmil
--	-------------------



Power Cable Termination Insulation Diameter	16.5 - 27 mm[.65 - 1.062 in]
Shed Inside Diameter	73.66 mm[2.9 in]
Sheath Outside Diameter	27.94 mm[1.1 in]
Length (Installed)	320.04 mm[12.6 in]

Usage Conditions

Operating Temperature Range	-40 - 40 °C
-----------------------------	-------------

Operation/Application

Application Type	Outdoor
------------------	---------

Industry Standards

Design Specification	HD CENELEC 629.1, IEEE 48
----------------------	---------------------------

Product Availability

Minimum Order Quantity	1
Power Cable Termination Product Availability	Americas

Packaging Features

Minimum Packaging Unit	1
------------------------	---

Other

Installation Instruction	English
--------------------------	---------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUN 2013 (144) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles'(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # CAT-BLMT

Mechanical Lugs: up to 84 kV



TE Part # CAT-CABLE-BREAKOUT

Heat Shrink Halogen-Free Cable Breakout Boots

TE Part # CAT-ALROC-TOOLING

ALROC Cable Preparation Tooling

Also in the Series | RAYCHEM CSTO



Power Cable Terminations(30)

Customers Also Bought



TE Part # 721359-000

Wraparound Sleeve for Cable Repair

Documents



Product Drawings

CSTO-152G

English

Datasheets & Catalog Pages

Raychem Cold Shrink Terminations CST Data Sheet - IEEE404

English