

Part Number : 1000570140

Series Number : 100057

Product Category : Specialty Wire and Cable

Product Description : Temp-Flex High-Performance Flat-Ribbon Cable, 10 Circuits, 1.00mm Pitch, 28 AWG, Silver Plated Copper, UL 20424, 7/36 Stranded Extruded FEP, Blue

Status : Active

Engineering Number : F2807S-10-0394-5

---

## Documents & Resources

### Drawings

Drawing 1000570140\_sd.pdf

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Specialty Wire and Cable
Series	100057
Description	Temp-Flex High-Performance Flat-Ribbon Cable, 10 Circuits, 1.00mm Pitch, 28 AWG, Silver Plated Copper, UL 20424, 7/36 Stranded Extruded FEP, Blue
Product Family	Temp-Flex Flat Ribbon Cable Solutions
Product Name	Temp-Flex
UPC	889056600262

## Electrical

Current - Maximum per Contact	1.5A
Voltage - Maximum	300V AC

## Physical

Cable Length	400 ft/spool, 10 ft min length, Any lengths/spool max
Circuits (Loaded)	10
Color - Cable Jacket	Blue
Insulation	FEP
Material - Outer Jacket	FEP
Material - Plating Mating	Silver
Net Weight	13.402/g
Packaging Type	Spool
Pitch - Mating Interface	1.00mm
Temperature Range - Operating	-55° to +200°C
Wire/Cable Type	7/36 Stranded, High-Performance Flat-Ribbon, UL 20424
Wire Size (AWG)	28

---

## Use with Part(s)

Description	Part Number
Use With	Molex Picoflex

---

---

This document was generated on May 24, 2024