NTD4302

MOSFET – Power, N-Channel, DPAK/IPAK
68 A, 30 V

Features

- Ultra Low $R_{DS(on)}$
- Higher Efficiency Extending Battery Life
- Logic Level Gate Drive
- Diode Exhibits High Speed, Soft Recovery
- Avalanche Energy Specified
- I_{DSS} Specified at Elevated Temperature
- DPAK Mounting Information Provided
- These Devices are Pb−Free and are RoHS Compliant

Applications

- DC−DC Converters
- Low Voltage Motor Control
- Power Management in Portable and Battery Powered Products: i.e., Computers, Printers, Cellular and Cordless Telephones, and PCMCIA Cards

MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	30	Vdc
Gate−to−Source Voltage − Continuous	V_{GS}	±20	Vdc
Thermal Resistance − Junction−to−Case Total Power Dissipation @ T_C = 25°C Continuous Drain Current @ T_C = 25°C (Note 4) Continuous Drain Current @ T_C = 100°C	$R_{\theta JC}$ P_D I_D I_D	1.65 75 68 43	°C/W W A A
Thermal Resistance − Junction−to−Ambient (Note 2) Total Power Dissipation @ T_A = 25°C Continuous Drain Current @ T_A = 25°C Continuous Drain Current @ T_A = 100°C Pulsed Drain Current (Note 3)	$R_{\theta JA}$ P_D I_D I_D I_{DM}	67 1.87 11.3 7.1 36	°C/W W A A A
Thermal Resistance − Junction−to−Ambient (Note 1) Total Power Dissipation @ T_A = 25°C Continuous Drain Current @ T_A = 25°C Continuous Drain Current @ T_A = 100°C Pulsed Drain Current (Note 3)	$R_{\theta JA}$ P_D I_D I_D I_{DM}	120 1.04 8.4 5.3 28	°C/W W A A A
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to 150	°C
Single Pulse Drain−to−Source Avalanche Energy − Starting T_J = 25°C (V_{DD} = 30 Vdc, V_{GS} = 10 Vdc, Peak I_L = 17 Apk, L = 5.0 mH, R_G = 25 Ω)	E_{AS}	722	mJ
Maximum Lead Temperature for Soldering Purposes, 1/8 in from case for 10 seconds	T_L	260	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. When surface mounted to an FR4 board using the minimum recommended pad size.
2. When surface mounted to an FR4 board using 0.5 sq. in. drain pad size.
3. Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2%.
4. Current Limited by Internal Lead Wires.


ON Semiconductor®

http://onsemi.com


$V_{(BR)DSS}$	$R_{DS(on)}$ TYP	I_D MAX
30 V	7.8 mΩ @ 10 V	68 A



N−Channel





DPAK
CASE 369C
(Surface Mount)
STYLE 2



IPAK
CASE 369D
(Straight Lead)
STYLE 2

MARKING DIAGRAMS & PIN ASSIGNMENTS





A	= Assembly Location*
Y	= Year
WW	= Work Week
T4302	= Device Code
G	= Pb−Free Package

* The Assembly Location code (A) is front side optional. In cases where the Assembly Location is stamped in the package, the front side assembly code may be blank.

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

© Semiconductor Components Industries, LLC, 2014

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−Source Breakdown Voltage		$V_{(BR)DSS}$				Vdc
(V_{GS} = 0 Vdc, I_D = 250 μA)			30	–	–	
Positive Temperature Coefficient			–	25	–	mV/°C
Zero Gate Voltage Drain Current		I_{DSS}				μAdc
(V_{GS} = 0 Vdc, V_{DS} = 30 Vdc, T_J = 25°C)			–	–	1.0	
(V_{GS} = 0 Vdc, V_{DS} = 30 Vdc, T_J = 125°C)			–	–	10	
Gate−Body Leakage Current (V_{GS} = ±20 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	–	–	±100	nAdc
ON CHARACTERISTICS						
Gate Threshold Voltage		$V_{GS(th)}$				Vdc
(V_{DS} = V_{GS}, I_D = 250 μAdc)			1.0	1.9	3.0	
Negative Temperature Coefficient			–	−3.8	–	
Static Drain−Source On−State Resistance		$R_{DS(on)}$				Ω
(V_{GS} = 10 Vdc, I_D = 20 Adc)			–	0.0078	0.010	
(V_{GS} = 10 Vdc, I_D = 10 Adc)			–	0.0078	0.010	
(V_{GS} = 4.5 Vdc, I_D = 5.0 Adc)			–	0.010	0.013	
Forward Transconductance (V_{DS} = 15 Vdc, I_D = 10 Adc)		gFS	–	20	–	Mhos
DYNAMIC CHARACTERISTICS						
Input Capacitance	(V_{DS} = 24 Vdc, V_{GS} = 0 Vdc, f = 1.0 MHz)	C_{iss}	–	2050	2400	pF
Output Capacitance		C_{oss}	–	640	800	
Reverse Transfer Capacitance		C_{rss}	–	225	310	
SWITCHING CHARACTERISTICS (Note 6)						
Turn−On Delay Time	(V_{DD} = 25 Vdc, I_D = 1.0 Adc, V_{GS} = 10 Vdc, R_G = 6.0 Ω)	$t_{d(on)}$	–	11	20	ns
Rise Time		t_r	–	15	25	
Turn−Off Delay Time		$t_{d(off)}$	–	85	130	
Fall Time		t_f	–	55	90	
Turn−On Delay Time	(V_{DD} = 25 Vdc, I_D = 1.0 Adc, V_{GS} = 10 Vdc, R_G = 2.5 Ω)	$t_{d(on)}$	–	11	20	ns
Rise Time		t_r	–	13	20	
Turn−Off Delay Time		$t_{d(off)}$	–	55	90	
Fall Time		t_f	–	40	75	
Turn−On Delay Time	(V_{DD} = 24 Vdc, I_D = 20 Adc, V_{GS} = 10 Vdc, R_G = 2.5 Ω)	$t_{d(on)}$	–	15	–	ns
Rise Time		t_r	–	25	–	
Turn−Off Delay Time		$t_{d(off)}$	–	40	–	
Fall Time		t_f	–	58	–	
Gate Charge	(V_{DS} = 24 Vdc, I_D = 2.0 Adc, V_{GS} = 10 Vdc)	Q_T	–	55	80	nC
		Q_{gs} (Q1)	–	5.5	–	
		Q_{gd} (Q2)	–	15	–	
BODY−DRAIN DIODE RATINGS (Note 5)						
Diode Forward On−Voltage		V_{SD}				Vdc
(I_S = 2.3 Adc, V_{GS} = 0 Vdc)			–	0.75	1.0	
(I_S = 20 Adc, V_{GS} = 0 Vdc)			–	0.90	–	
(I_S = 2.3 Adc, V_{GS} = 0 Vdc, T_J = 125°C)			–	0.65	–	
Reverse Recovery Time	(I_S = 2.3 Adc, V_{GS} = 0 Vdc, dI_S/dt = 100 A/μs)	t_{rr}	–	39	65	ns
		t_a	–	20	–	
		t_b	–	19	–	
Reverse Recovery Stored Charge		Q_{rr}	–	0.043	–	μC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. Indicates Pulse Test: Pulse Width = 300 μsec max, Duty Cycle ≤ 2%.
6. Switching characteristics are independent of operating junction temperature.

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate−To−Source Voltage




Figure 4. On−Resistance vs. Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Drain−To−Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current

TYPICAL CHARACTERISTICS




Figure 11. Maximum Rated Forward Biased Safe Operating Area




Figure 12. Diode Reverse Recovery Waveform




Figure 13. Thermal Response − Various Duty Cycles


ORDERING INFORMATION

Device	Package Type	Package	Shipping†
NTD4302G	DPAK	369C (Pb−Free)	75 Units / Rail
NTD4302−1G	IPAK	369D (Pb−Free)	75 Units / Rail
NTD4302T4G	DPAK	369C (Pb−Free)	2500 Tape & Reel


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

IPAK
CASE 369D–01
ISSUE C

DATE 15 DEC 2010



SCALE 1:1



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.235	0.245	5.97	6.35
B	0.250	0.265	6.35	6.73
C	0.086	0.094	2.19	2.38
D	0.027	0.035	0.69	0.88
E	0.018	0.023	0.46	0.58
F	0.037	0.045	0.94	1.14
G	0.090 BSC		2.29 BSC	
H	0.034	0.040	0.87	1.01
J	0.018	0.023	0.46	0.58
K	0.350	0.380	8.89	9.65
R	0.180	0.215	4.45	5.45
S	0.025	0.040	0.63	1.01
V	0.035	0.050	0.89	1.27
Z	0.155	---	3.93	---

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 3:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE


STYLE 4:
PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

STYLE 5:
PIN 1. GATE
2. ANODE
3. CATHODE
4. ANODE

STYLE 6:
PIN 1. MT1
2. MT2
3. GATE
4. MT2

STYLE 7:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

MARKING DIAGRAMS



xxxxxxxxx = Device Code
A = Assembly Location
IL = Wafer Lot
Y = Year
WW = Work Week


DOCUMENT NUMBER:	98AON10528D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	IPAK (DPAK INSERTION MOUNT)	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®



SCALE 1:1

DPAK (SINGLE GUAGE)
CASE 369AA−01
ISSUE B

DATE 03 JUN 2010



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.086	0.094	2.18	2.38
A1	0.000	0.005	0.00	0.13
b	0.025	0.035	0.63	0.89
b2	0.030	0.045	0.76	1.14
b3	0.180	0.215	4.57	5.46
c	0.018	0.024	0.46	0.61
c2	0.018	0.024	0.46	0.61
D	0.235	0.245	5.97	6.22
E	0.250	0.265	6.35	6.73
e	0.090 BSC		2.29 BSC	
H	0.370	0.410	9.40	10.41
L	0.055	0.070	1.40	1.78
L1	0.108 REF		2.74 REF	
L2	0.020 BSC		0.51 BSC	
L3	0.035	0.050	0.89	1.27
L4	−−−	0.040	−−−	1.01
Z	0.155	−−−	3.93	−−−

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 3:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE


STYLE 4:
PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

STYLE 5:
PIN 1. GATE
2. ANODE
3. CATHODE
4. ANODE

STYLE 6:
PIN 1. MT1
2. MT2
3. GATE
4. MT2

STYLE 7:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR


SOLDERING FOOTPRINT*



SCALE 3:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



IC Discrete

XXXXXX = Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
WW = Work Week
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking.

DOCUMENT NUMBER:	98AON13126D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	DPAK (SINGLE GAUGE)	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales