SPORT-2X2-S1

~10° spot beam.



SPECIFICATION:

Dimensions	50.0 x 50.0 mm
Height	16 mm
Fastening	screw
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length
SPORT-2X2-S1	Multi-lens	PMMA	clear		50.0

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C17991_SPORT-2X2-S1 » Box size: 480 x 280 x 300 mm	512	128	32	10.8

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XP-G4
FWHM / FWTM	9.0° / 20.0°
Efficiency	96 %
Peak intensity	24.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON HL2X
FWHM / FWTM	10.0° / 21.0°
Efficiency	97 %
Peak intensity	21.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON HL2X
FWHM / FWTM	10.0° / 21.0°
Efficiency	97 %
Peak intensity	21.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON HL2X
FWHM / FWTM	10.0° / 21.0°
Efficiency	94 %
Peak intensity	20.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass





Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ C 3030
FWHM / FWTM	9.0° / 19.0°
Efficiency	96 %
Peak intensity	23.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	9.0° / 18.0°
Efficiency	97 %
Peak intensity	27.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

TEPCOMP group

LED	PassivePAQ-R-274x51-NI0-21K-857-5
FWHM / FWTM	15.0° / 27.0°
Efficiency	96 %
Peak intensity	10.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	J Series 5050 Round LES
FWHM / FWTM	16.0° / 32.0°
Efficiency	95 %
Peak intensity	8.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	J Series 5050 Round LES
FWHM / FWTM	16.0° / 32.0°
Efficiency	87 %
Peak intensity	7.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	J Series 5050B 6V K Class
FWHM / FWTM	16.0° / 34.0°
Efficiency	95 %
Peak intensity	7.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	J Series 5050B 6V K Class
FWHM / FWTM	18.0° / 34.0°
Efficiency	87 %
Peak intensity	6.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	J Series 5050C 6V E Class
FWHM / FWTM	16.0° / 32.0°
Efficiency	96 %
Peak intensity	8.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



CREE LEDs

LED	XD16
FWHM / FWTM	8.0° / 16.0°
Efficiency	87 %
Peak intensity	28.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XHP35.2 HD
FWHM / FWTM	16.0° / 34.0°
Efficiency	95 %
Peak intensity	7.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP35.2 HD
FWHM / FWTM	18.0° / 34.0°
Efficiency	86 %
Peak intensity	6.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

CREE LEDs

LED	XHP35.2 HI
FWHM / FWTM	14.0° / 28.0°
Efficiency	87 %
Peak intensity	10.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XHP35.2 HI
FWHM / FWTM	14.0° / 26.0°
Efficiency	95 %
Peak intensity	11.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP50.3 HI
FWHM / FWTM	14.0° / 28.0°
Efficiency	95 %
Peak intensity	10.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP50.3 HI
FWHM / FWTM	14.0° / 28.0°
Efficiency	87 %
Peak intensity	9.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XM-L3
FWHM / FWTM	12.0° / 26.0°
Efficiency	95 %
Peak intensity	12.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XM-L3
FWHM / FWTM	12.0° / 28.0°
Efficiency	87 %
Peak intensity	11 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

CREE LEDs

LED	XP-E
FWHM / FWTM	6.0° / 14.0°
Efficiency	95 %
Peak intensity	52.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XP-G2
FWHM / FWTM	10.0° / 20.0°
Efficiency	90 %
Peak intensity	21.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	XP-G2 HE
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	28.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XP-G2 HE
FWHM / FWTM	10.0° / 20.0°
Efficiency	91 %
Peak intensity	23.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XP-G3
FWHM / FWTM	10.0° / 22.0°
Efficiency	95 %
Peak intensity	18.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XP-G3
FWHM / FWTM	10.0° / 22.0°
Efficiency	86 %
Peak intensity	16.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	XP-G4 HI
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	29.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XP-G4 HI
FWHM / FWTM	8.0° / 18.0°
Efficiency	87 %
Peak intensity	23.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

CREE LEDs

LED	XP-L HD
FWHM / FWTM	12.0° / 26.0°
Efficiency	90 %
Peak intensity	12.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	XP-L HD
FWHM / FWTM	12.0° / 26.0°
Efficiency	95 %
Peak intensity	13.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XP-L HI
FWHM / FWTM	8.0° / 18.0°
Efficiency	96 %
Peak intensity	26.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XP-L HI
FWHM / FWTM	10.0° / 20.0°
Efficiency	87 %
Peak intensity	22.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

CREE LEDs

LED	XP-L2
FWHM / FWTM	14.0° / 28.0°
Efficiency	95 %
Peak intensity	10.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XP-L2
FWHM / FWTM	14.0° / 28.0°
Efficiency	86 %
Peak intensity	9.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	XP-P
FWHM / FWTM	8.0° / 14.0°
Efficiency	86 %
Peak intensity	39.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

CREE LEDs

LED	XP-P
FWHM / FWTM	6.0° / 14.0°
Efficiency	95 %
Peak intensity	52.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON 3030 2D (Round LES)
FWHM / FWTM	8.0° / 18.0°
Efficiency	90 %
Peak intensity	27.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

LUMILEDS

LED	LUXEON 5050 HE
FWHM / FWTM	16.0° / 32.0°
Efficiency	95 %
Peak intensity	8.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON 5050 Round LES
FWHM / FWTM	18.0° / 34.0°
Efficiency	87 %
Peak intensity	6.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON 5050 Round LES
FWHM / FWTM	18.0° / 34.0°
Efficiency	95 %
Peak intensity	7.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON 5050 Square LES
FWHM / FWTM	20.0° / 36.0°
Efficiency	90 %
Peak intensity	5.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

LUMILEDS

LED	LUXEON 5050 Square LES
FWHM / FWTM	20.0° / 36.0°
Efficiency	95 %
Peak intensity	6.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON 7070
FWHM / FWTM	22.0° / 48.0°
Efficiency	93 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON HL2X
FWHM / FWTM	10.0° / 22.0°
Efficiency	95 %
Peak intensity	21 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON HL2X
FWHM / FWTM	10.0° / 22.0°
Efficiency	87 %
Peak intensity	18.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON HL2X-D
FWHM / FWTM	12.0° / 26.0°
Efficiency	96 %
Peak intensity	15.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON HL2X-D
FWHM / FWTM	12.0° / 26.0°
Efficiency	88 %
Peak intensity	13.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

LUMILEDS

LED	LUXEON HL2X-P
FWHM / FWTM	12.0° / 26.0°
Efficiency	95 %
Peak intensity	15.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON HL2Z
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	27.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON XR-HL2X (L2H2-xxxxxxxMLU010)
FWHM / FWTM	12.0° / 24.0°
Efficiency	96 %
Peak intensity	16.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON XR-HL2X (L2H2-xxxxxxxMLU010)
FWHM / FWTM	12.0° / 24.0°
Efficiency	88 %
Peak intensity	14.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMINUS

LED	SFT-40-WCS
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	30.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMINUS

LED	SFT-70X-WCS
FWHM / FWTM	10.0° / 22.0°
Efficiency	96 %
Peak intensity	18.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMINUS

LED	SST-20
FWHM / FWTM	8.0° / 16.0°
Efficiency	89 %
Peak intensity	30.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMINUS

LED	SST-70X-WCS
FWHM / FWTM	16.0° / 30.0°
Efficiency	87 %
Peak intensity	8.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LUMINUS

LED	SST-70X-WCS
FWHM / FWTM	16.0° / 30.0°
Efficiency	96 %
Peak intensity	8.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	NFMW48xA
FWHM / FWTM	18.0° / 34.0°
Efficiency	95 %
Peak intensity	7.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NV4WB35AM
FWHM / FWTM	14.0° / 26.0°
Efficiency	87 %
Peak intensity	10.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

NICHIA

LED	NV4WB35AM
FWHM / FWTM	14.0° / 26.0°
Efficiency	96 %
Peak intensity	11.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	NVSW219D
FWHM / FWTM	10.0° / 22.0°
Efficiency	90 %
Peak intensity	19.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NVSW219F
FWHM / FWTM	10.0° / 22.0°
Efficiency	90 %
Peak intensity	17.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



NICHIA

LED	NVSW219F
FWHM / FWTM	10.0° / 22.0°
Efficiency	95 %
Peak intensity	19.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

NICHIA

LED	NVSW219F
FWHM / FWTM	10.0° / 22.0°
Efficiency	95 %
Peak intensity	20.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NVSW519A
FWHM / FWTM	12.0° / 27.0°
Efficiency	94 %
Peak intensity	13.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	NVSxE21A
FWHM / FWTM	8.0° / 18.0°
Efficiency	88 %
Peak intensity	27.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

OSRAM
Opto Semiconductors

LED	DURIS E 5050 (GW J9LHS1.4M)
FWHM / FWTM	14.0° / 32.0°
Efficiency	95 %
Peak intensity	9.5 cd/lm
LEDs/each optic	1
Light colour/type	RGBW
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	Duris S5 (2 chip)
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	27.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



OSRAM
Opto Semiconductors

LED	Duris S5 (Single chip)
FWHM / FWTM	6.0° / 14.0°
Efficiency	95 %
Peak intensity	45.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



OSRAM
Opto Semiconductors

LED	Duris S8
FWHM / FWTM	20.0° / 38.0°
Efficiency	95 %
Peak intensity	5.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	Duris S8
FWHM / FWTM	22.0° / 40.0°
Efficiency	87 %
Peak intensity	4.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ C 3030
FWHM / FWTM	10.0° / 20.0°
Efficiency	96 %
Peak intensity	24.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



OSRAM
Opto Semiconductors

LED	OSCONIQ C 3030
FWHM / FWTM	10.0° / 20.0°
Efficiency	87 %
Peak intensity	20.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSCONIQ P 3737 (2W version)
FWHM / FWTM	8.0° / 18.0°
Efficiency	90 %
Peak intensity	26.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ P 3737 (3W version)
FWHM / FWTM	12.0° / 24.0°
Efficiency	96 %
Peak intensity	15.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ P 3737 (3W version)
FWHM / FWTM	12.0° / 24.0°
Efficiency	87 %
Peak intensity	14.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSLON Optimal (GF CSSRML.24)
FWHM / FWTM	6.0° / 14.0°
Efficiency	92 %
Peak intensity	41.9 cd/lm
LEDs/each optic	1
Light colour/type	Far Red
Required components:	



Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	10.0° / 20.0°
Efficiency	86 %
Peak intensity	19.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	28.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LH351B
FWHM / FWTM	10.0° / 20.0°
Efficiency	96 %
Peak intensity	22.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG

LED	LH351B
FWHM / FWTM	10.0° / 22.0°
Efficiency	87 %
Peak intensity	19.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

SAMSUNG

LED	LH351C
FWHM / FWTM	10.0° / 22.0°
Efficiency	96 %
Peak intensity	18.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LH351C
FWHM / FWTM	10.0° / 22.0°
Efficiency	88 %
Peak intensity	16.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

SAMSUNG

LED	LH351D
FWHM / FWTM	14.0° / 28.0°
Efficiency	95 %
Peak intensity	11.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG

LED	LH351D
FWHM / FWTM	14.0° / 28.0°
Efficiency	90 %
Peak intensity	10.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LH502C
FWHM / FWTM	18.0° / 35.0°
Efficiency	90 %
Peak intensity	6.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

SAMSUNG

LED	LH502C
FWHM / FWTM	18.0° / 36.0°
Efficiency	95 %
Peak intensity	6.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SEOUL SEMICONDUCTOR

LED	Z5M4
FWHM / FWTM	10.0° / 22.0°
Efficiency	90 %
Peak intensity	18 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SEOUL SEMICONDUCTOR

LED	Z8Y22
FWHM / FWTM	10.0° / 22.0°
Efficiency	86 %
Peak intensity	16.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Protective plate, glass



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.