6437288-6 ✔ ACTIVE

AMP | SUPERSEAL 1.0mm

TE Internal #: 6437288-6

PCB Mount Header, Vertical, Wire-to-Board, 26 Position, 3 mm [.118 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, SUPERSEAL 1.0mm

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles > SUPERSEAL Connector Headers: 1.0 mm







Connector System: **Wire-to-Board**

Number of Positions: **26**

Centerline (Pitch): **3 mm [.118 in]**

Sealable: **Yes**

PCB Mount Orientation: **Vertical**

All SUPERSEAL Connector Headers: 1.0 mm (23)

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Board
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Sections	1
Number of Signal Positions	26
Number of Positions	26
PCB Mount Orientation	Vertical
Number of Rows	4

Electrical Characteristics

Voltage Rating (Max)	250 VAC
Nominal Voltage Architecture	250 V
Operating Voltage	250 VAC

Body Features

Primary Product Color	Black

Contact Features

Contact Size	1mm
Contact Type	Pin
Mating Pin Diameter	1 mm[.039 in]
Contact Mating Area Plating Material	Gold

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Mounting Holes	Without
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Locking Interface

Housing Features

Centerline (Pitch)	3 mm[.118 in]

Dimensions

Connector Length	36.5 mm[1.43 in]
Connector Width	39 mm[1.53 in]
Profile Height from PCB	24.7 mm[.972 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]

Operation/Application

Shielded	No
Circuit Application	Signal

Packaging Features

Packaging Quantity	17
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 3-1437290-7
26POS,SUPERSEAL,REC HSG ASSY, SLD,COD 1

Also in the Series | SUPERSEAL 1.0mm



Automotive Housings(14)




Automotive Terminals(6)



Connector Backshells(2)




Connector Seals & Cavity Plugs(1)



PCB Headers & Receptacles(33)


Customers Also Bought



TE Part # 3-641216-9
09P MTA100 HDR ASSY FL/RA LF



TE Part # 6-66460-6
PIN,.062 DIA,.025 SQ POST,LP



TE Part # 953472-1
26pos MQS .63 header 180deg THR



TE Part # 6318745-3
025 32 Pos Cap Assy H Au



TE Part # 2-2399610-2
2POS,HVP1400,ASSY,90DEG,COD C/D



TE Part # 2-2399610-5
2POS,HVP1400,ASSY,90DEG,COD J/K



TE Part # 2066008-1
2P SUPERSEAL 1.5 SERIES TAB AS

TE Part # 3-2394033-2
HD-20 PLUG 15P SMT UNC 4-40 THD, W/O STUD

Documents

Product Drawings

26POS,AMP SUPERSEAL 1.0MM,PIN HSG ASSY

Japanese

26POS,AMP SUPERSEAL 1.0MM,PIN HSG ASSY

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_6437288-6_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6437288-6_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6437288-6_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Receptacle Contact, Super Seal Connector

Japanese

Application Specification

Japanese

Super Seal Connector

Japanese

Application Specification

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

English

SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR

English

Agency Approvals

UL Report

English