



MQS

TE Internal #: 1719059-1
Housing for Female Terminals, Wire-to-Wire, 32 Position, .1 in [2.54 mm] Centerline, Natural, Wire & Cable, Signal, Cable Mount (Free-Hanging), MQS

[View on TE.com >](#)

Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Connector System: **Wire-to-Wire**
Number of Positions: **32**
Connector & Housing Type: **Housing for Female Terminals**
Centerline (Pitch): **2.54 mm [.1 in]**
Sealable: **No**

[All MQS, CONNECTOR HOUSING \(435\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	32
Number of Rows	2

Electrical Characteristics

Operating Voltage	12 VAC
-------------------	--------



Nominal Voltage Architecture	12 V, 24 V
------------------------------	------------

Body Features

Cable Exit Angle	90°
Primary Product Color	Natural
Connector & Keying Code	Neutral

Contact Features

Contact Size	.63mm
Contact Type	Receptacle
Mating Tab Width	.63 mm[.025 in]
Contact Current Rating (Max)	7.5 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Connector Height	13 mm[.512 in]
Product Width	16.5 mm[.65 in]
Product Length	42.6 mm[1.68 in]
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]

Operation/Application

Conforms to KOMAX Automatic Component Insertion Guideline	Yes, per Version 5.0 (March 2018)
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------



Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




TE Part # CAT-SIGH262
Signal Header



TE Part # CAT-M8793-T273
MQS, RECEPTACLE AND TAB



TE Part # 2278196-2
MQS COVER ASS'Y, 2X16 POSN.



TE Part # 1-2278196-1
MQS COVER ASS'Y, 2X16 POSN.



TE Part # 2-966658-3
32pos MQS .63 header 180deg

TE Part # 2050723-1
COVER FOR MQS HSG 2x16 POS ASSY

TE Part # 2278196-1
MQS COVER ASS'Y, 2X16 POSN.

TE Part # 2050723-5
COVER FOR MQS HSG 2x16 POS ASSY

TE Part # 9-966658-9
PIN HEADER, ASSY 2X16POS.

Also in the Series | MQS

Automotive Connector Caps & Covers (113)

Automotive Connector EMC Shielding (3)

Automotive Connector Locks & Position Assurance(26)

Automotive Housings(379)

Automotive Terminals(88)

Connector Seals & Cavity Plugs(26)

Insertion & Extraction Tools(42)

Other Automotive Connector Accessories(7)

PCB Headers & Receptacles(143)

Customers Also Bought



TE Part # 1534579-1
16POS MQS REC COD A

TE Part # 368502-1
070 MLC PLUG HSG 6P SGL

TE Part # 1241846-2
TIMER, RECEPTACLE AND TAB

TE Part # 1241394-3
AMP MCP 2.8K, CONTACT, SWS

TE Part # 5-1241608-1
MQS1,5 Sn rec CB unseal. 0,75-1,5

TE Part # 1813712-9
81P ECU KIT

TE Part # 6-1355118-1
MQS VERRIEGLUNG

TE Part # 1-969489-2
6POS MQS REC COD A

TE Part # 2188504-1
025/110 HYB 8P PLUG ASS'Y

Documents

Product Drawings
32POS MQS REC

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_1719059-1_A_c-1719059-1-a.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_1719059-1_A_c-1719059-1-a.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_1719059-1_A_c-1719059-1-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages



Micro Quadlok Interconnection System (MQS)

English

Product Specifications

Application Specification

English