2359615-5 ✔ ACTIVE

TE Internal #: 2359615-5

ANSI Street Lighting Receptacles, Accessory, -40 - 85 °C [-40 - 185 °F]

View on TE.com >

Connectors > Lighting Connectors > Street Lighting Controls > Street Lighting Receptacles






Lighting Product Type: **Accessory**

Operating Temperature Range: **-40 - 85 °C [-40 - 185 °F]**

Features

Product Type Features

Lighting Product Type	Accessory

Usage Conditions

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]

Industry Standards

Compatible With Agency/Standards Products	ANSI

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: UV-329 (1% in Component Part) **Article Safe Usage Statements:** Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900

	ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2359482-1
LUMAWISE ENDURANCE N+ 7P Base With Vent



TE Part # 2359482-2
LUMAWISE ENDURANCE N+ 7P Base



TE Part # 2359482-3
LUMAWISE ENDURANCE N+ 5P Base With Vent



TE Part # 2359482-4
LUMAWISE ENDURANCE N+ 5P Base



TE Part # 2359482-5
LUMAWISE ENDURANCE N+ 3P Base With Vent



TE Part # 2359482-6
LUMAWISE ENDURANCE N+ 3P Base

Customers Also Bought



TE Part # 794610-1
MICRO MNL RPT CNT,LS PC,TIN



TE Part # 3-640599-4
04P MTA156 CONN ASSY 18AWG ORA



TE Part # 2359482-1
LUMAWISE ENDURANCE N+ 7P Base With Vent

Documents

Product Drawings

LUMAWISE ENDURANCE N+ Clear Short Dome

English

CAD Files

Customer View Model

ENG_CVM_CVM_2359615-5_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2359615-5_A1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2359615-5_A1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

LUMAWISE ENDURANCE N+ Network Lighting Controls

English

Product Specifications

Application Specification

English

Agency Approvals

UL_CERT_CB_4789600659_TR_C1

English

UL_CERT_CB_US_37285_C1

English