6-2355626-1 ✔ ACTIVE

TE Internal #: 6-2355626-1

DIMM Sockets, Double Data Rate (DDR) 5, Board-to-Component, 288 Position, Surface Mount, Vertical Module Orientation, .033 in [.85 mm] Centerline

View on TE.com >

Connectors > Socket Connectors > Memory Sockets > DIMM Sockets



DRAM Type: **Double Data Rate (DDR) 5**

Connector System: **Board-to-Component**

Number of Positions: **288**

Termination Method to Printed Circuit Board: **Surface Mount**

Module Orientation: **Vertical**

Features

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
DRAM Type	Double Data Rate (DDR) 5
Connector System	Board-to-Component

Configuration Features

Number of Bays	2
Number of Keys	1
Number of Rows	2
Number of Positions	288
Module Orientation	Vertical

Electrical Characteristics

DRAM Voltage	1.1 V

Body Features

PCB Retention Feature Material	Stainless Steel
Ejector Material Color	Black

Ejector Material	High Temperature Nylon
Latch Color	Black
Ejector Location	Both Ends
Latch Material	High Temperature Nylon
Module Key Type	DRAM
Connector Profile	Standard
Ejector Type	Rotary

Contact Features

Memory Socket Type	Memory Card
Socket Style	DIMM
PCB Contact Termination Area Plating Material Thickness	3 µm[120 µin]
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]
Contact Mating Area Plating Material	Gold
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	1.5 A

Termination Features

Insertion Style	Direct Insert
Termination Post & Tail Length	.89 mm[.035 in]
Termination Method to Printed Circuit Board	Surface Mount

Mechanical Attachment

Mount Angle	Vertical
PCB Mount Alignment Type	None
Mating Alignment Type	1 Key
Mating Alignment	With
PCB Mount Retention Type	Tab
Connector Mounting Type	Board Mount

Housing Features

Housing Material	High Temperature Nylon
Housing Color	Black
Centerline (Pitch)	.85 mm[.033 in]

Dimensions

Profile Height from PCB	21.3 mm[.083 in]
Row-to-Row Spacing	3 mm[.118 in]

Usage Conditions

Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]

Operation/Application

Circuit Application	High Speed Data

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	640
Packaging Method	Box & Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 6-2355632-1
DDR5 DIMM NATURAL HSG AND NATURAL LATCH


Customers Also Bought



TE Part # 1-111626-9
20, 2MM, 30 DP, LEAD FREE



TE Part # 100751-1
Z-PACK/N M-HSG 3P.



TE Part # 8-2176364-2
RQ 0402 32K4 0.1% 10PPM 5K RL



TE Part # 2-1416010-9
RY212060



TE Part # 203422-E
MJ LSS * * 8 8 * * * STP GURT 30 * J 3 2



TE Part # 203512-E
MJ HS V5 * 8 8 * * * * 999999 30 * J 3 1



TE Part # 5-966443-4
4 POS. MOD II PIN HDR, SGL ROW



TE Part # 8-5102321-0
A/L UNIV HDR 50P VERT SPECIAL LG LAT

Documents

Product Drawings

DDR5 DIMM BLACK HSG AND BLACK LATCH

English

CAD Files

Customer View Model

ENG_CVM_CVM_6-2355626-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-2355626-1_A.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_6-2355626-1_A.3d_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English