




VAL-U-LOK

TE Internal #: 1586044-4
Standard Rectangular Connectors, Connector Assembly, Plug,
Mating Alignment, Keyed Mating Alignment Type, Mating
Retention, Wire-to-Board, Tin, Normal

[View on TE.com >](#)

Connectors > Rectangular Connectors > Standard Rectangular Connectors



Connector Product Type: **Connector Assembly**
Connector & Housing Type: **Plug**
Mating Alignment: **With**
Mating Alignment Type: **Keyed**
Mating Retention: **With**

Features

Product Type Features

Connector Product Type	Connector Assembly
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Insertion Force Type	Normal
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Contacts Preloaded	Yes
PCB Mount Orientation	Right Angle
Number of Positions	4
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features



Contact Layout	Inline
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Tin
Contact Retention Within Housing	Without
Contact Current Rating (Max)	9 A

Termination Features

Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment	Without
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Hole
Mating Alignment	With
Mating Alignment Type	Keyed
Mating Retention	With
Mating Retention Type	Latch
Connector Mounting Type	Board Mount

Housing Features

Housing Material	Nylon GF
Housing Color	Natural
Centerline (Pitch)	4.19 mm[.165 in]

Dimensions

Connector Height	9.8 mm[.386 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Product Width	13 mm[.512 in]
Product Length	9.6 mm[.378 in]
Row-to-Row Spacing	4.2 mm[.165 in]
Compatible Insulation Diameter Range	1.2 - 3.1 mm[.047 - .122 in]
Wire Size	.12 - 1.4 mm²

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
-----------------------------	----------------------------



Operation/Application

Shielded	No
Circuit Application	Power

Identification Marking

Circuit Identification Feature	With
--------------------------------	------

Industry Standards

CSA Rating	208567
UL Rating	Recognized
Glow Wire Rating	Standard Part - Not Glow Wire
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Method	Box & Tray, Tray
------------------	------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits









as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Part # 1586019-4 4P RCPT VAL-U-LOK V0</p>	 <p>TE Part # 1969613-4 4P PM PLUG VAL-U-LOK V0</p>	 <p>TE Part # 1969612-4 4P FH PLUG VAL-U-LOK V0</p>	 <p>TE Part # 794318-1 AMP DUAC/PL 04P KIT BULK PKG</p>
---	--	--	--

Customers Also Bought

 <p>TE Part # T4140012051-000 M12,REAR MOUNTING,MALE,A CODE,5P</p>	 <p>TE Part # 5788799-1 15 HTMSFL ASSY RA 318 (SL,BL)</p>	 <p>TE Part # 5788797-1 09 HTMSFL ASSY RA 318 (SL,BL)</p>	 <p>TE Part # 350826-1 04P UMNL HDR ASSY PC 94VO</p>
 <p>TE Part # 292207-3 MINI CT SGL DIP V 3P NAT</p>	 <p>TE Part # 3-1879354-7 RR03 5% 10R AMMO</p>	 <p>TE Part # 4-1879354-7 RR03 5% 27R AMMO</p>	 <p>TE Part # 1586044-2 2P VAL-U-LOK R/A HDR SCR MT V0</p>
 <p>TE Part # 1586044-6 6P VAL-U-LOK R/A HDR SCR MT V0</p>	 <p>TE Part # 1879207-1 RN 0603 200K 0.1% 10PPM 5K RL</p>		

Documents

Product Drawings
4P VAL-U-LOK R/A HDR SCR MT V0

English



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1586044-4_A_c-1586044-4-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1586044-4_A_c-1586044-4-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1586044-4_A_c-1586044-4-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English