



Connectors > PCB Connectors > PCB Headers & Receptacles > DYNAMIC 1900D HDR ASSY



Connector System: **Wire-to-Board**

Number of Positions: **38**

Number of Rows: **2**

Centerline (Pitch): **3.5 mm [.137 in]**

PCB Mount Orientation: **Horizontal**

[All DYNAMIC 1900D HDR ASSY \(9\)](#)

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Number of Positions	38
Number of Rows	2
PCB Mount Orientation	Horizontal

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Mating Area Plating Material Thickness	.38 µm[15 µin]
--	----------------



Contact Mating Area Plating Material	Gold
Contact Type	Pin
Contact Current Rating (Max)	1 A

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder
---	-----------------------

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
PCB Mount Retention Type	Retention Leg
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With

Housing Features

Housing Material	Polyester GF
Centerline (Pitch)	3.5 mm [.137 in]

Usage Conditions

Operating Temperature Range	-30 - 105 °C [-22 - 221 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Box, Tube
------------------	-----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240)



Candidate List Declared Against: JAN 2024
(240)
Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 2-1871946-9
DYNAMIC 1900D REC HSG CRIMP
TYPE 38p

Also in the Series

Dynamic 1000 Series

			
Connector Contacts(40)	Connector Hardware(3)	Insertion & Extraction Tools(2)	PCB Headers & Receptacles(172)



Rectangular Connector Housings(2)



Standard Rectangular Connectors(1)




Wire-to-Board Connector Assemblies & Housings(159)

Customers Also Bought



TE Part # 5179029-6
0.8FH,P06H.5,140,08/Sn,TU



TE Part # 5499160-2
A/L UNIV HDR 14P VERT SHT LAT



TE Part # 2-1410271-0
MULTIGIG RT PWR .8" R/A HDR 4P
PBFR



TE Part # 292303-1
Std USB Type A, R/A, T/H



TE Part # 176976-1
AMP UNIVERSAL POWER PLG 3C PCB



TE Part # 643426-1
09P UMNL SOK HDR ASSY POL 94VO



TE Part # 3-2176091-3
RP 2A 0.25W 124R 0.1% 25PPM 1K RL



TE Part # 292254-3
CT RELAY HDR ASSY 3P NAT

Documents

Product Drawings

DYNAMIC 1900D HDR ASSY H-TYPE 38P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1871935-9_D_c-2-1871935-9-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1871935-9_D_c-2-1871935-9-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1871935-9_D_c-2-1871935-9-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



Datasheets & Catalog Pages

DYNAMIC SPRING CLAMP SERIES

- English
- DYNAMIC SPRING CLAMP SERIES
- Japanese

Product Specifications

Product Specification

- Japanese

Agency Approvals

UL Report

- English