350586-1 ✔ ACTIVE

MATE-N-LOK | Universal MATE-N-LOK




TE Internal #: 350586-1

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 9 Position, 6.35 mm [.25 in] Centerline, Printed Circuit Board, Universal MATE-N-LOK

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **9**

Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	9
PCB Mount Orientation	Vertical
Number of Power Positions	9
Number of Rows	3

Electrical Characteristics

Operating Voltage	600 VAC

Contact Features

Multiple Contact Types	Without

PCB Contact Termination Area Plating Material Thickness	2.54 µm[100 µin]
Contact Layout	Matrix
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	10 A, 12 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Pre-Tin
Contact Mating Area Plating Material Thickness	3.81 - 5.08 µm[150 - 200 µin]

Termination Features

Termination Post & Tail Length	3.05 mm[.12 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Positive Lock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]
Row-to-Row Spacing	6.35 mm[.25 in]

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]

Operation/Application

Circuit Application	Power

Industry Standards

UL Rating	Recognized
Compatible With Agency/Standards Products	UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 350812-1
STR/REL CLAMP UMNL



TE Part # 1-640722-0
09P UMNL STR/REL & INSRT NATL



TE Part # 794277-1
09P UMNL INTERFACE SEAL



TE Part # 640716-1
09P UMNL STR/REL & INSRT



TE Part # 927231-3
HONHUS UMNL V0 9-P



TE Part # 1-350590-0
STR/REL CLAMP NATL



TE Part # 643749-1
06P UMNL HDR ASSY W/O DRNS



TE Part # 927231-5
UNML CAP HSG 9WAY




TE Part # 794994-1
09P UMNL BLACK INTERFACE SEAL



TE Part # 1-480706-0
09P UMNL PLUG HSG NATL



TE Part # 794278-1
09P UMNL WIRE SEAL



TE Part # 1969818-1
09P UMNL PIN HDR ASSY NATL, PIN V0 GW



TE Part # 1586853-1
09P UMNL CAP HSG, GW



TE Part # 1586879-1
09P UMNL SKT HDR ASSY, GW



TE Part # 643254-1
09P UMNL ASSY MOD HSG VO




TE Part # 794538-1
09P UMNL CAP HSG 150C BLK



TE Part # 1969882-1
09P UMNL CAP HSG, P/M, GW V0



TE Part # 2029299-1
9 POS UMNL CAP W/LARGE FLANGE-V0



TE Part # 2029315-1
09P UMNL CAP HSG 150C-RED

Also in the Series | Universal MATE-N-LOK



Circular Power Connectors(2)



Connector Caps & Covers(34)



Connector Contacts(209)



Connector Hardware(12)



Connector Seals & Cavity Plugs(27)



Connector Strain Relief(7)



Insertion & Extraction Tools(4)



Rectangular Connector Housings(1)



Rectangular Power Connectors(671)




Standard Circular Connectors(1)


Customers Also Bought




TE Part # 3-641190-3
03P MTA100 CONN ASSY RED LF



TE Part # 5499910-6
A/L UNIV HDR 26P VERT SHT LAT



TE Part # 1-1658526-1
609-1641LF FEM SOCKT,LEAD FREE



TE Part # 1-480284-0
08P CMNL CAP HSG M/M NATL



TE Part # 1-6609016-8
15ED1=F7801 S0



TE Part # 4-1609037-3
20EH6=F8367



TE Part # 3-641218-4
04P MTA156 CONN ASSY 20AWG LF



TE Part # 3-641151-2
02P MTA156 ASSY 24AWG WHT LF

Documents

Product Drawings

09P UMNL PIN HDR ASSY V2 NATL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_350586-1_Y.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_350586-1_Y.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_350586-1_Y.3d_stp.zip

English

3D PDF

English

Customer View Model

ENG_CVM_350586-1_T.3d_igs.zip

English

Customer View Model

ENG_CVM_350586-1_T.3d_stp.zip

English

Customer View Model

ENG_CVM_350586-1_T.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English