T4081122004-000 ACTIVE



M8 Connector

TE Internal #: T4081122004-000

Standard Circular Connectors, Cable-to-Cable, 4 Position, Sealable,

Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse

Gender, M8 Connector

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 4

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Features

Product Type Features

| Troduct Type realures | |
|---------------------------------------|----------------------|
| Product Type | Connector Assembly |
| Accessory Color | Black |
| Assembly Requirement | Factory Assembled |
| Assembly Type | Electrical Connector |
| Circular Connector Shell Type | All Plastic |
| Connector Product Type | Connector Assembly |
| Connector System | Cable-to-Cable |
| Sealable | Yes |
| Connector & Contact Terminates To | Wire & Cable |
| Circular Connector Type | Plug |
| Shell Type | Plastic |
| Configuration Features | |
| Keying & Polarized Position Locations | A |
| | |

No

Factory Installed Backshell



| Keying | A |
|--|---|
| Number of Positions | 4 |
| Number of Power Positions | 0 |
| Number of Signal Positions | 4 |
| Contacts Preloaded | Yes |
| Electrical Characteristics | |
| Operating Voltage | 30 VAC |
| Body Features | |
| Peripheral Seal Material | Silicone |
| Environmental Protection | IP67 |
| O-Ring Material | Silicone |
| Environmental Protection Type | Sealed |
| Shell Plating Material | Unplated |
| Shell Base Material | Plastic |
| Circular Connector Insulation Material Type | Polyamide 66 GF25 |
| Hermetically Sealed | Yes |
| | |
| Contact Features | |
| | 4 A |
| Contact Features | 4 A Yes |
| Contact Features Contact Current Rating (Max) | |
| Contact Features Contact Current Rating (Max) Reverse Gender | Yes |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type | Yes |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment | Yes Pin |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type | Yes Pin Cable Mount (Free-Hanging) |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code | Yes Pin Cable Mount (Free-Hanging) A |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type | Yes Pin Cable Mount (Free-Hanging) A |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions | Yes Pin Cable Mount (Free-Hanging) A Keyed |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level | Yes Pin Cable Mount (Free-Hanging) A Keyed |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level | Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67 |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range | Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67 |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range Operation/Application | Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67 -40 - 85 °C[-40 - 185 °F] |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Polarization Code Mating Alignment Type Usage Conditions IP Dust Sealing Level IP Water Sealing Level Operating Temperature Range Operation/Application Durability Rating | Yes Pin Cable Mount (Free-Hanging) A Keyed 6 IP67 -40 - 85 °C[-40 - 185 °F] 100 Cycles |



Industry Standards

| UL Flammability Rating | UL 94HB |
|------------------------|---------|
| Packaging Features | |
| Packaging Quantity | 1 |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Also in the Series | M8 Connector









Connector Hardware(4)

M8/M12 Cable Assemblies(147)

Customers Also Bought















Documents

Product Drawings M8 Y DISTRIBUTOR MALE 4POS

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_T4081122004-000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_T4081122004-000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4081122004-000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Application Specification

English

Application Specification

English

Agency Approvals

UL

English