


- NOTE:
1. TEST:DC 300V/1s
 2. INSULATION RESISTANCE:10m ohm
 3. CONTACT RESISTANCE:2 ohm
 4. PRODUCTS MEASURE UP TO THE ROHS
 5. PVC TEGUMENT

9	PE BAG 6"*9"*0.04MM	1PCS
8	ELLIPTICAL CABLE TIE WITH CORE L=70MM	1PCS
7	TIN WIRE LEAD-FREE Ø0.6 ROHS	0.45g
6	P1&P2 PVC , BLACK 45P	10g
5	CONDUCTIVE COPPER PLATINIUM P1& P2.W:20MM*L:35MM	2PCS
4	GUMMED PAPER W:15MM	0.07m
3	PE1&P2 TRANSPARENT PE INTERNAL MODEL MATERIALS,LOW DENSITY	4g
2	HDMI C TYPE MALE : SHORT BODY PIN G/F,IRON SHELL-PLATED NICKEL,INSULATION BLACK	2PCS
1	UL20276[30AWG(7/0.10TS)*1P+EA+AL/MY]*4+30AWG(7/0.10TS)*1P+30AWG(7/0.10TS)*5G+AE[16/6/0.12AM] OD:6.0mm PVC BLACK TEGUMENT CUT L=990±10mm(LS)	1PCS
No	DESCRIPTION	QTY



Cnc Tech, LLC

-TOLERANCES-
公差參考表
UNLESS OTHERWISE SPECIFIED

TITLE: HDMI CM TO CM CABLE PVC

X.X	±0.38	X.X°	±3.00°	APPD:	PRODUCT NO: 742-20010-00200
X.XX	±0.25	X.XX°	±2.00°	CHECK:	DATE
X.XXX	±0.10	X.XXX°	±1.00°	DRAW:	SCALE
					UNIT
					TYPE
					PAGE
					1 / 1

1 2 3 4 5 6 7 8 9 10