



Aavid - The worldwide leader in thermal management solutions

News About Aavid Contact Us Global Manufacturing Shop Aavid

Products

Solutions

Industries

Search Aavid

Register or Sign Into Your Account

Cart

Knowledge Center

Design Help

Interface Materials

- > Gap Fillers
- > Thermal Greases
 - > Sil-Free
 - > Ther-O-Link
 - > Thermalcote
 - > Thermalcote II
- > Thermal Adhesives & Epoxies
- > Attachment Tapes
- > Insulating Hardware
- > Insulating Pads & Films
- > Non-Insulating Pads & Films
- > Phase Change Materials

Thermalcote™ Thermal Grease

Thermalcote (Part #: 249, 250G, 251G, 252G, and 253G)

Thermalcote is a superior silicone-based thermal joint compound uniquely developed to increase heat transfer to all heat sinks. Thermalcote's thermal conductivity is more than 15 times that of air and more than 4 times the conductivity of typical silicone-based greases. It is non-toxic and extremely stable; it neither cakes nor runs between -40°C to 204°C.

Available sizes:

Thermalcote is available in a 28 g (1 oz) and 57 g (2 oz) tube as well as a 0.45 kg (1 lb) can.

[» MSDS Safety Sheet for Thermalcote in PDF format 41K](#)

Thermalcote Resistance Calculator

Enter the area of the device that will contact the heat sink:	<input type="text"/>	mm ²
Enter the grease thickness:	<input type="text"/>	mm
<input type="button" value="Calculate"/>		
Interface Resistance =	<input type="text"/>	

Formula

$$\text{interface resistance} = \frac{\text{interface thickness (mm)} * 1000}{\text{thermal conductivity (W/m-K)} * \text{contact area (mm}^2\text{)}}$$

Color	Opaque White
Operating Temperature Range	-40°C to 204°C (-40°F to 399°F).
Thermal Conductivity	0.765Wm-1°C-1 (0.442 Btu/hr ft °F)
Dialectic strength 1.27 mm gap(0.050" gap)	11.8 x 103volts/mm (300volts/mil)
Cleaning solvent	Mineral Spirits or Turpentine
Specific gravity	1.6
Evaporation, 24 hours@200°C (392°F), wt%	1
Shelf Life	Indefinite1 (unopened) One Year (opened)

(1) It is recommended that the containers be turned over every 6 months to minimize settling for ease of mixing.

Ordering Information

Part No.	RoHS	PCN	Net Weight
249			28 grams (1 oz) tube
250G			57 grams (2 oz) tube
251G			.45Kg. (1 lb) can
252G			2.27Kg. (5 lbs) can
253G			4.54Kg. (10 lbs) can

Need assistance?

Call us: 1-855-32-AAVID
Email: estore@aavid.com

[» Help Page](#)

Check Distributor Stock

Enter a part number for pricing and availability.

- > [Request a Sample](#)
- > [Request a Quote](#)
- > [Ask an Engineer](#)




Request a quote for a custom shape or size

[Request a Quote](#)

Thermalcote II (discontinued)

Thermalcote II (349G,350G,351G has been discontinued

Thermalcote II has been discontinued. Please see our Sil-Free product line for a suitable replacement.

Part No.	PCN
349G No longer available	
350G No longer available	
351G No longer available	

Customer Assistance

- [Contact Us](#)
- [Get Design Assistance](#)
- [Find a Distributor](#)
- [Find a Sales Rep](#)
- [Request a Quote](#)
- [Placing an Order](#)
- [Terms and Conditions](#)
- [Returns](#)

Popular Products

- [Fans](#)
- [Extrusions](#)
- [Board Level](#)
- [Liquid Cooling](#)
- [Heat Pipe Technology](#)
- [Heat Sink Accessories](#)
- [Interface Materials](#)

Our Company

- [News and Events](#)
- [Management Team](#)
- [Worldwide Locations](#)
- [Directions to USA Headquarters](#)
- [Disclaimer](#)
- [Customer Survey](#)
- [Privacy Policy](#)
- [Careers](#)

Connect with Aavid

Sign up for Aavid News & Alerts

Like / Follow / Connect



© Copyright 2015 Aavid Thermalloy, LLC.

USA: 1.855.32.AAVID Europe: 39.051.764002 Asia: 86.21.6115.2000 x 8122