
Multilayer Ceramic Chip Capacitor

Part Number: C22CF121G-BZN-X1T

Description: C22 2500Vdc 120pF ±2% NP0 Porcelain - Hi Q Single-side marked

A range of high frequency, High Q capacitors for multiple challenging applications such as DC Blocking, Impedance Matching, Coupling, Bypass and Frequency Discrimination (Filtering). The CF Ultra Temperature Stable range is designed for temperature sensitive, frequency sensitive and time sensitive applications.



Mechanical Specification

Size Code	C22 (2225 package)
Length (L1) in mm (")	5.734 ± 0.667 (0.226 ± 0.026)
Width (W) in mm (")	6.37 ± 0.699 (0.251 ± 0.028)
Thickness (T) in mm (")	3.467 Max (0.137 Max)
Minimum Termination Band (L2,L3) in mm (")	0.356 (0.014)
Maximum Termination Band (L2,L3) in mm (")	1.372 (0.054)
Termination Material	Nickel Barrier, Sn Plated Solder (RoHS compliant)
Solderability	Per MIL-STD-202, Method 208
Packaging	7" Reel Horizontal Orientation, 500 per reel

General Electrical Specification

Rated Voltage	2500Vdc
Nominal Capacitance Value	120pF
Capacitance Tolerance	±2%
Tangent of Loss Angle (Tan δ)	≤0.0005
Capacitance and Tan δ Test Conditions	1.0Vrms @ 1MHz
Voltage Proof (Voltage applied for 5 secs max. @ 50mA max. charge current)	6250Vdc (3750Vdc if marked)
Min Insulation Resistance (IR)	1000.00GOhm @ 1000Vdc
Dielectric Classification	NP0 Porcelain - Hi Q
Rated Temperature Range	-55°C / +125°C
Maximum Capacitance Change over Temperature Range	No DC Voltage 0±15ppm/°C Rated DC Voltage -
Climatic Category (IEC)	-
Ageing Characteristic	Zero

Knowles Precision Devices - Sales
Europe: KPD-Europe-sales@knowles.com
Asia: KPD-Asia-sales@knowles.com
USA: KPD-NA-sales@knowles.com
www.knowlescapacitors.com

This datasheet is for a standard item and is confirmed valid on the date generated, the latest published data for this part may differ and is available at http://www.knowlescapacitors.com or by contacting us.

© The information contained on this drawing is confidential and may not be copied in whole or part in any form or disclosed to a third party without the consent of Knowles and any customer mentioned within this specification.

Data is correct to the best of our knowledge, errors and omissions excepted.

Date: Tuesday, October 03, 2023

20231003 180643875UTC

Multilayer Ceramic Chip Capacitor

Part Number: C22CF121G-BZN-X1T	**Description:** C22 2500Vdc 120pF ±2% NP0 Porcelain - Hi Q Single-side marked

Environmental

RoHS Compliant to 2011/65/EC as amended by 2015/863/EU	Compliant
REACH Compliant	235 compliant
California Proposition 65	No exposure risk


Board Layout

Knowles' conventional 2-terminal chip capacitors can generally be mounted using pad designs in accordance with international specification IPC-7351, Generic Requirements for Surface Mount Design and Land Pattern Standards, but there are some other factors that have been shown to reduce mechanical stress, such as reducing the pad width to less than the chip width. In addition, the position of the chip on the board should be considered.

Some high voltage parts may require modifications to the board layout and/or the addition of a conformal coating to prevent flashover. Refer to application note AN0043 for further information.

IPC-7351 pad design


	C22 (2225 package)	
C	4.98mm	0.196"
Y	2.18mm	0.086"
X	7.32mm	0.288"



Packaging

Tape packaging information for tape-and-reel parts:

Tape and reel packing of surface mounting chip capacitors for automatic placement are in accordance with IEC60286-3.




Soldering

Reflow solder in accordance with IPC-A-610. Recommended reflow profile as laid down in IPC/JEDEC J-STD-020.

Wave soldering is also possible, but care must be taken for case sizes 1210 and larger and component thickness >1.0mm. Trials are encouraged.

Hand soldering is not recommended and can lead to component damage through thermal shock.

PdAg terminations are primarily intended for conductive epoxy attachment - they may be suitable for soldering but trials are recommended.



Application notes with mounting and handling guidance are available on request.

Compex DLI Johanson MFG Novacap Syfer Voltronics

Knowles Precision Devices - Sales

Europe: KPD-Europe-sales@knowles.com

Asia: KPD-Asia-sales@knowles.com

USA: KPD-NA-sales@knowles.com

www.knowlescapacitors.com

This datasheet is for a standard item and is confirmed valid on the date generated, the latest published data for this part may differ and is available at http://www.knowlescapacitors.com or by contacting us.

© The information contained on this drawing is confidential and may not be copied in whole or part in any form or disclosed to a third party without the consent of Knowles and any customer mentioned within this specification.

Data is correct to the best of our knowledge, errors and omissions excepted.

Date: Tuesday, October 03, 2023

20231003 180643875UTC