



CII

TE Internal #: 1617132-7

TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C /O, 5VDC Input Voltage, 5VDC Coil Voltage Rating, 100Ω Coil Resistance

[View on TE.com >](#)

Relays & Contactors > Relays > Mil-Aero Relays > TO-5/.100 Grid Relays



Contact Arrangement: 2 Form C, DPDT, 2 C/O

Input Voltage: 5 VDC

Coil Voltage Rating: 5 VDC

Coil Resistance: 100 Ω

Coil Power Rating DC: 250 mW

Features

Configuration Features

Coil Special Features	Coil Polarity Protection Diode, Coil Suppression Diode
Contact Arrangement	2 Form C, DPDT, 2 C/O

Electrical Characteristics

Contact Current Rating	1 A
Contact Switching Voltage (Max)	28 VDC
Input Voltage	5 VDC
Coil Voltage Rating	5 VDC
Coil Resistance	100 Ω
Coil Power Rating DC	250 mW

Body Features

Enclosure Type	Hermetically Sealed
----------------	---------------------

Termination Features

Relay Connection Type	Flying Leads
-----------------------	--------------

Usage Conditions

Operating Temperature Range	-65 - 125 °C
-----------------------------	--------------

Operation/Application

--



Vibration Resistance	30G's, 10 - 3000Hz
Actuating System	DC
Shock Resistance	75G's, 6ms
Coil Magnetic System	Non-Polarized, Monostable

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-1617031-3
[HFW1201K46](#) = [M39016/6-209L](#)



Customers Also Bought

TE Part # 640456-7
07P MTA100 HDR ASSY F/L SQ STR

TE Part # 2-521105-2
ULTRA-FAST 187 ASY REC 22-18 TPBR

TE Part # 87165-2
LOCKING CLIP ASSY .025 SQ LP

TE Part # 6-1879354-8
RR03 5% 200R AMMO

TE Part # 5-2176329-2
CRGP 1210 180K 1%

TE Part # 806878-000
222D232-25-0

TE Part # 9-1617352-7
JMAPDD-6XL=M39016/20-038L

TE Part # 5-1393788-8
V23079D1005B301

TE Part # 1617031-2
HFW1201K03 = HFW 1/2 SIZE RELA

TE Part # TSE-22-01
JUNCTION ASSY

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1617132-7_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1617132-7_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1617132-7_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

5-1773450-5_sec1_MS

English



RELAY

English