

VMT38-25-3/8-55-Z/10PK

Ruland VMT38-25-3/8-55-Z/10PK, 10 Pack Of Rubber Bumpers, 1.50" OD, 3/8X16 Tapped Hole, 0.39" Tapped Hole Depth, 0.98" Height, 55 Shore A Natural Rubber Jacket, Steel

10 pack





Description

Ruland VMT38-25-3/8-55-Z/10PK is a 10 pack of rubber bumpers, each with a tapped hole. An individual rubber bumper has 1.50" outside diameter, 3/8x16 tapped hole, 0.39" tapped hole depth, and 0.98" height. Rubber bumpers are used to dampen shock loads and reduce noise and wear on industrial equipment, machine doors, and floors or other surfaces which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. These rubber bumpers have a cylindrical shape allowing for even distribution of shock loads. A rubber bumper can be mounted to the system by threading it onto an existing stud on the components. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. Rubber bumpers in this pack have 55 Shore A hardness for a balance of rigidity and shock absorption. Bodies are made from zinc plated steel allowing for high strength suitability in most industrial applications. These rubber bumpers are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	1.50 in (38 mm)	**Height (H1)**	0.98 in (25 mm)
Thread (TH)	3/8 in - 16 TPI	**Plate Thickness (PT)**	0.08 in (2 mm)
Tapped Hole Depth (LT)	0.39 in (9.9 mm)	**Spring Rate**	1599.98 lb/in (280.2 N/mm)
Shore Hardness	55A (+/- 5)	**Max Deflection**	0.25 in (6.4 mm)
Max Axial Load	400 lb (1779.3 N)	**Multipack Quantity**	10
Geometry	Cylindrical	**Rubber Material**	Natural Rubber
Metal Material	Zinc Plated Steel	**Metallic Body Finish**	Zinc-Plated
Country of Origin	Hungary	**Weight (lbs)**	1.133000
UPC	634529313220	**Tariff Code**	4016.99.6000
UNSPC	31162804		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	⚠**WARNING** This product can expose you to the chemical Soots		