
FSR12-3-3-A

Ruland FSR12-3-3-A, 3/16" x 3/16" Six Beam Coupling, Aluminum, Set Screw Style, 0.750" OD, 1.250" Length





Description

Ruland FSR12-3-3-A is a set screw style six beam coupling with 0.1875" x 0.1875" bores, 0.750" OD, and 1.250" length. It is machined from a single piece of material and features two sets of three spiral cuts. This gives it higher torque capacity, lower windup, and larger body sizes than single or four beam couplings and allows for use in light duty power transmission applications such as coupling a servo motor to a lead screw. FSR12-3-3-A is zero-backlash and has a balanced design for reduced vibration at high speeds of up to 6,000 RPM. All hardware is metric and tests beyond DIN 912 12.9 standards for maximum torque capabilities. FSR12-3-3-A is made from 7075 aluminum for lightweight and low inertia. It is machined from bar stock that is sourced exclusively from North American mills and RoHS3 and REACH compliant. FSR12-3-3-A is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	0.1875 in	**Small Bore (B2)**	0.1875 in
B1 Max Shaft Penetration	0.607 in	**B2 Max Shaft Penetration**	0.607 in
Outer Diameter (OD)	0.750 in	**Bore Tolerance**	+0.001 in / -0.000 in
Length (L)	1.250 in	**Recommended Shaft Tolerance**	+0.0000 in / -0.0005 in
Forged Set Screw	M4	**Screw Material**	Alloy Steel
Hex Wrench Size	2.0 mm	**Screw Finish**	Black Oxide
Seating Torque	1.76 Nm	**Number of Screws**	2 ea
Dynamic Torque Reversing	6.5 lb-in	**Angular Misalignment**	3.0°
Dynamic Torque Non-Reversing	13 lb-in	**Parallel Misalignment**	0.008 in
Static Torque	26 lb-in	**Axial Motion**	0.005 in
Torsional Stiffness	0.152 Deg/lb-in	**Moment of Inertia**	0.0036 lb-in^2
Maximum Speed	6,000 RPM	**Full Bearing Support Required?**	Yes
Zero-Backlash?	Yes	**Torque Wrench**	TW:BT-1R-1/4-15.6
Recommended Hex Key	Metric Hex Keys	**Material Specification**	7075-T651 Extruded and Drawn Aluminum Bar
Temperature	-40°F to 225°F (-40°C to 107°C)	**Finish Specification**	Bright, No Plating
Manufacturer	Ruland Manufacturing	**Country of Origin**	USA
Weight (lbs)	0.045900	**UPC**	634529011447
Tariff Code	8483.60.8000	**UNSPC**	31163003
Note 1	Torque ratings are at maximum misalignment.		
Note 2	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Note 3	Torque ratings for the couplings are based on the physical limitations/failure point of the machined beams. Under normal/typical conditions the hubs are capable of holding up to the rated torque of the machined beams. In some cases, especially when the smallest standard bores are used or where shafts are undersized, slippage on the shaft is possible below the rated torque of the machined beams. Please consult technical support for more assistance.		
Prop 65	⚠**WARNING** This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		

Installation Instructions

1. Align the bores of the FSR12-3-3-A six beam coupling on the shafts that are to be joined and determine if the misalignment parameters are within the limits of the coupling. (*Angular*

Misialignment: 3°, *Parallel Misalignment*: 0.008 in, *Axial Motion*: 0.005 in)

2. Fully tighten the M4 screws on one hub to the recommended seating torque of 1.76 Nm using a 2.0 mm hex torque wrench.
3. Before tightening the screws on the second hub, rotate the coupling by hand to allow it to reach its free length.
4. Tighten the screws on the second hub to the recommended seating torque. Make sure the coupling remains axially relaxed and the misalignment angle remains centered along the length of the coupling.
5. The shafts may extend into the relieved portion of the bore as long as it does not exceed the shaft penetration length of 0.607 in.