
JCC21-6-A

Ruland JCC21-6-A, 3/8" Jaw Coupling Hub, Aluminum, Clamp Style With Keyway, 1.313" OD, 0.590" Length





Description

Ruland JCC21-6-A is a clamp zero-backlash jaw coupling hub with a 0.3750" bore, 3/32" keyway, 1.313" OD, and 0.590" length. It is a component in a three-piece design consisiting of two aluminum hubs and an elastomeric insert called the spider creating a lightweight low inertia coupling capable of speeds up to 8,000 RPM. This three-piece design allows for a highly customizable coupling that easily combines clamp or set screw hubs with inch, metric, keyed, and keyless bores. Spiders are available in three durometers allowing the user to tailor coupling performance to their application. Ruland jaw couplings have a balanced design for reduced vibration at high speeds. Hardware is metric and tests beyond DIN 912 12.9 standards for maximum torque capabilities. JCC21-6-A is machined from bar stock that is sourced exclusively from North American mills and is RoHS3 and REACH compliant. It is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	0.3750 in	**Keyway (K)**	3/32 in
B1 Max Shaft Penetration	0.590 in	**Outer Diameter (OD)**	1.313 in (33.3 mm)
Bore Tolerance	+0.001 in / -0.000 in	**Hub Width (LH)**	0.590 in
Length (L)	1.750 in (44.5 mm)	**Recommended Shaft Tolerance**	+0.0000 in / -0.0005 in
Forged Clamp Screw	M3	**Number of Screws**	1 ea
Screw Material	Alloy Steel	**Screw Finish**	Black Oxide
Hex Wrench Size	2.5 mm	**Seating Torque**	2.1 Nm
Torque Specifications	Torque ratings vary with insert selection	**Misalignment**	Misalignment ratings vary with insert selection
Maximum Speed	8,000 RPM	**Moment of Inertia**	0.019386 lb-in^2
Full Bearing Support Required?	Yes	**Recommended Inserts**	JD21/33-98R, JD21/33-92Y, JD21/33-85B
Zero-Backlash?	Yes	**Balanced Design**	Yes
Fail Safe?	Yes	**Weight (lbs)**	0.079000
Temperature	-10°F to 180°F (-23°C to 82°C)	**Material Specification**	2024-T351 Aluminum Bar
Finish	Bright	**Finish Specification**	Bright, No Plating
Manufacturer	Ruland Manufacturing	**Recommended Gap Between Hubs**	0.030 in (0.75 mm)
Country of Origin	USA	**UPC**	634529113196
UNSPC	31163011	**Tariff Code**	8483.60.8000
Note 1	Stainless steel hubs are available upon request.		
Note 2	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Note 3	Torque ratings for the couplings are based on the physical limitations/failure point of the spiders. Under normal/typical conditions the hubs are capable of holding up to the nominal torque of the spiders. Please consult technical support for more assistance.		
Prop 65	⚠**WARNING** This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		

Installation Instructions

1. Align the bores of the JCC21-6-A jaw coupling hubs on the shafts that are to be joined and determine if the misalignment parameters are within the limits of the coupling. (See spider for misalignment parameters.)

2. Fully tighten the M3 screw(s) on the first hub to the recommended seating torque of 2.1 Nm using a 2.5 mm hex torque wrench.
3. Insert a spider into the jaws of one hub until the raised points contact the base of the hub.
4. Insert the jaws of the second hub into the spider openings until the raised points contact the base of the second hub. Some force will be required to insert the second hub. This is normal.
5. Assure that a gap is maintained between the two hubs so there is no metal to metal contact. Fully tighten the screw(s) on the second hub to the recommended seating torque.