LA63-5/16X18-ZF

Ruland Adjustable Clamping Lever, Lever Length 63mm, Tapped Hole 5/16X18, Zinc Lever, Steel Inserts





Description

Ruland LA63-5/16X18-ZF is an adjustable clamping handle with a 63mm handle, 5/16X18 tapped hole, 13.5mm insert diameter, and 45mm overall height. The steel inserts combined with a zinc die-cast handle allow for use in heavy duty industrial applications. LA63-5/16X18-ZF has a textured finish on the handle making it easy for the user to grip in manufacturing environments with oil, coolant, or other lubricants. It is commonly found in packaging, printing, food processing, and manufacturing systems where conveyor rails, sensors, screens, and other components require frequent adjustments without the use of tools. The adjustable feature of this handle allows it to be used in confined spaces with limited hand access or where 360 degree rotation is not possible. Serrations connect the insert to the handle for easy disengagement. The user pulls the handle upwards by hand to disengage the serrations allowing it to be swiveled to the desired clamping position. Serrations automatically re-engage once the user releases the handle locking it in-place. A 5/16X18 tapped hole is designed to mate with an equivalently sized threaded stud or rod for a quick installation. LA63-5/16X18-ZF is black to seamlessly integrate with the aesthetics of most equipment. It is manufactured by Otto Ganter, stocked by Ruland, and RoHS3 and REACH compliant.

Product Specifications

Thread (TH)	5/16 in - 18 TPI	**Lever Length L1**	63 mm
Overall Height H1	45 mm	**Hub Height H2**	31 mm
Hub Diameter DH	17.5 mm	**Handle Disengagement Travel H3**	4 mm
Thread Depth T	11 mm	**Sleeve Length L2**	6.5 mm
Sleeve Diameter D1	13.5 mm	**Handle Material**	Zinc
Handle Color	Black	**Insert and Screw Material**	Steel
Insert and Screw Finish	Blackened	**Weight (lbs)**	0.163100
Manufacturer	JW Winco/ Otto Ganter	**UPC**	634529236260
Country of Origin	Germany	**Tariff Code**	8487.90.0080
UNSPC	31162807		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	⚠**WARNING** This product can expose you to chemicals including Soots, Benzene, Lead, and Nickel (metallic), known to the State of California to cause cancer, and Lead and Benzene known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		