
MT12-CGRC-85S-PS

Conveyor Guide Clamp With Rod, Stainless Steel Rod, 17mm (0.67 in) Channel Width, 12mm Rod OD, 85mm Rod Length





Description

Ruland MT12/12-CB2W-A is a two-way base connector with a 38mm base diameter, 12mm round thru holes, a 10mm square thru hole, M5 clamp screws, and an overall length of 25mm. The base is aluminum and the screws are 304 stainless steel. The two-way base connector is typically used as a base in support structures for mounting sensors, plexiglass guards, or other applications. It is designed for tubes that have the same thru hole size. The clamping force of the clamp onto the tube is achieved via the socket cap screws but you can choose to replace these with adjustable lever clamp kits that have the same screw size. It is RoHS3 and REACH compliant.#html-body [data-pb-style="60B6E4375D4E4"]{justify-content: flex-start; display: flex; flex-direction: column; background-position: left top; background-size: cover; background-repeat: no-repeat; background-attachment: scroll; border-style: none; border-width: 1px; border-radius: 0px; margin: 0px 0px 10px; padding: 10px;}#html-body [data-pb-style="60B6E4375D500"]{border-style: none; border-width: 1px; border-radius: 0px; margin: 0px; padding: 0px;}

Product Specifications

Channel Width	17 mm (0.67 in)	**Rod Diameter**	12 mm
Rod Length	85 mm	**Clamp Length L1**	31.5 mm
Clamp Width WC	27 mm	**Clamp Height**	37 mm
Clamp Screw CL	M5	**Screw Material**	304 Stainless Steel
Rod Material	304 Stainless Steel	**Weight (lbs)**	0.242500
Manufacturer	JW Winco/ Otto Ganter	**UPC**	634529314708
Country of Origin	Spain	**Tariff Code**	7609.00.0000
UNSPC	31162908		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	⚠**WARNING** This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.		